

ISO 13679:2002-12 (E)

Petroleum and natural gas industries - Procedures for testing casing and tubing connections

Contents		Page
Foreword		vi
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	2
3.1	Terms and definitions	2
3.2	Symbols and abbreviated terms	4
4	General requirements	8
4.1	Connection geometry, test load envelope and performance data sheet	8
4.2	Quality control	9
5	General test requirements	9
5.1	Test classes	9
5.2	Test matrix	10
5.3	Test programme	14
5.4	Calibration and accreditation requirements	15
5.5	Rehearsal tests	16
5.6	Material property tests	16
5.7	Make-up and break-out procedures	17
5.8	Internal pressure leak detection	18
5.9	Internal pressure leak trap device	18
5.10	External pressure leak detection	25
5.11	Data acquisition and test methods	28
5.12	Thermal cycling tests	30
6	Connection test specimen preparation	32
6.1	General connection test objectives	32
6.2	Connection test specimen identification and marking	33
6.3	Connection test specimen preparation	33
6.4	Connection test specimen machining	35
6.5	Machining tolerances	36
6.6	Tolerance limits on machining objectives	37
6.7	Grooved torque shoulder	37
7	Test procedures	38
7.1	Principle	38
7.2	Make-up/break-out tests	38
7.3	Test load envelope tests	40
7.4	Limit load tests	52
7.5	Limit load test path (see Figures 18 and 19)	55
8	Acceptance criteria	57
8.1	Make-up and break-out tests	57
8.2	Test load envelope tests	58
8.3	Limit load tests	58

9	Test reports	59
	Annex A (normative) Connection geometry and performance data sheet	60
	Annex B (informative) Connection test load envelope and limit loads	67
	Annex C (normative) Data forms	85
	Annex D (normative) Connection full test report	115
	Annex E (normative) Connection testing summary report	118
	Annex F (informative) Frame load range determination	121
	Annex G (informative) Interpolation and extrapolation considerations	122
	Annex H (informative) Special application testing	124
	Annex I (informative) Rationale for design basis	130
	Annex J (normative) Independent seal testing of connections with metal-to-metal and resilient seals	133
	Bibliography	139
	Table 1 -- Test matrix -- Test series and specimen identification numbers	11
	Table 2 -- Connection test specimen objectives for all CAL	32
	Table 3 -- Guidelines for selecting connection test specimens for testing a metal-to-metal sealing, tapered thread connection with a torque shoulder	33
	Table 4 -- Tolerance limits on machining objectives	36
	Table 5 -- Specimen description and summary of test series for a metal-to-metal sealing, tapered thread connection with a torque shoulder	38
	Table 6 -- Test Series A load steps (see Figures 13 or 14, as applicable) -- Testing in quadrants I, II, III, IV (no bending) at ambient temperature	42
	Table 7 -- Test Series B load steps without bending for connection rated equal to pipe body (see Figure 15) -- Testing in quadrants I and II without bending at ambient temperature	46
	Table 8 -- Test Series B load steps with bending for connection rated equal to pipe body (see Figure 16) -- Testing in quadrants I and II with bending at ambient temperature	47
	Table A.1 -- Connection geometry and performance property data sheet	61
	Table A.2 -- Example Series A test load envelope for a connection rated equal to pipe body -- 178 mm D xxxx 10,16 mm wall thickness xxxx grade P-110 (7 in 29 lb/ft P-110) strength (see Figure A.1)	62
	Table A.3 -- Detailed load steps	63
	Table B.1 -- Areas and dimensions	70
	Table B.2 -- Required dimensions for critical cross-section computation	84
	Table F.1 -- Typical results from frame load range determination (200 kN to 2 000 kN)	121
	Figure 1 -- Connection application level test programme	12

Figure 2 -- Collared leak trap device for internal pressure leak detection	19
Figure 3 -- Flexible boot leak trap device for internal pressure leak detection	20
Figure 4 -- Ported box leak trap device for internal pressure leak detection	20
Figure 5 -- Internal pressure leak detection by bubble method	22
Figure 6 -- Example of a plot for determining leak detection sensitivity	23
Figure 7 -- Leak detection by helium mass spectrometer method	24
Figure 8 -- Example set-up for Test Series A	25
Figure 9 -- Example of leak detection system for Test Series A	26
Figure 10 -- Test Series C thermal/mechanical cycles for CAL II, III, and IV	30
Figure 11 -- Connection test specimen nomenclature and unsupported length	34
Figure 12 -- Torque shoulder pressure bypassing grooves	37
Figure 13 -- Test Series A load path for connection rated greater than or equal to pipe body in compression	44
Figure 14 -- Test Series A load path for connection rated less than pipe body in compression	45
Figure 15 -- Test Series B load paths without bending for connection rated equal to pipe body	49
Figure 16 -- Test Series B load paths with bending for connection rated equal to pipe body	50
Figure 17 -- Test Series B load paths for connection rated less than pipe body in compression and with bending	51
Figure 18 -- Limit load test paths for connections rated equal to or stronger than pipe body	53
Figure 19 -- Limit load test paths for connections weaker than pipe body	54
Figure B.1 -- Pipe body and connection test load envelopes at specified dimensions	68
Figure C.1 -- Recommended layout of mother joints for test and material specimens	86
Figure G.1 -- Example premium connection design space	123
Figure J.1 -- Ported box leak trap device for internal pressure leak detection showing modifications for resilient seal	135
Figure J.2 -- Connection acceptance levels with resilient seal ring	136
Figure J.3 -- Alternative testing sequence for a connection with metal-to-metal (MTM) and resilient seal (RS) features	138