

ISO 13503-5:2006-07 (E)

Petroleum and natural gas industries - Completion fluids and materials - Part 5: Procedures for measuring the long-term conductivity of proppants

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative reference | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Abbreviations | 2 |
| 5 | Procedures for evaluating long-term proppant pack conductivity | 2 |
| 5.1 | Objective | 2 |
| 5.2 | Discussion | 2 |
| 6 | Reagents and materials | 3 |
| 6.1 | Test fluid | 3 |
| 6.2 | Sandstone | 3 |
| 7 | Long-term conductivity test apparatus | 3 |
| 7.1 | Test unit | 3 |
| 7.2 | Hydraulic load frame | 3 |
| 7.3 | Pack width measurement device(s) | 3 |
| 7.4 | Test fluid drive system | 3 |
| 7.5 | Differential pressure transducers | 4 |
| 7.6 | Back-pressure regulators | 4 |
| 7.7 | Balance | 4 |
| 7.8 | Oxygen removal | 4 |
| 7.9 | Temperature control | 4 |
| 7.10 | Silica saturation and monitoring | 5 |
| 8 | Equipment calibration | 5 |
| 8.1 | Pressure indicators and flow rates | 5 |
| 8.2 | Zero pack width measurement | 5 |
| 8.3 | Determination of cell width | 6 |
| 8.4 | Hydraulic load frame | 6 |
| 9 | Leak tests | 6 |
| 9.1 | Hydraulic load frame | 6 |
| 9.2 | Test fluid system | 6 |
| 10 | Procedure for loading the cells | 6 |
| 10.1 | Preparation of the test unit | 6 |
| 10.2 | Cell setup | 7 |
| 11 | Loading cell(s) in the press | 9 |
| 12 | Acquiring data | 9 |
| 13 | Calculation of permeability and conductivity | 10 |

| | | |
|-----------|---|-----------|
| 14 | Data reporting | 11 |
| | Annex A (informative) Conversion factors | 12 |
| | Annex B (normative) Silica-saturation vessel setup | 13 |
| | Annex C (informative) Figures | 15 |
| | Bibliography | 24 |