

ISO 13503-2:2006-11 (E)

Petroleum and natural gas industries - Completion fluids and materials - Part 2: Measurement of properties of proppants used in hydraulic fracturing and gravel-packing operations

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Abbreviations	1
4	Standard proppant sampling procedure	2
4.1	General	2
4.2	Particle segregation	2
4.3	Equipment	2
4.4	Number of required samples -- Bulk	4
4.5	Sampling --Bulk material	5
4.6	Sampling -- Bagged material	5
5	Sample handling and storage	5
5.1	Sample reduction	5
5.2	Sample splitting	5
5.3	Sample and record retention and storage	5
6	Sieve analysis	6
6.1	Purpose	6
6.2	Description	6
6.3	Equipment and materials	6
6.4	Procedure	6
6.5	Calculation of the mean diameter, median diameter and standard deviation	7
6.6	Sieve calibration	9
7	Proppant sphericity and roundness	11
7.1	Purpose	11
7.2	Description	12
7.3	Apparatus capability	12
7.4	Procedure	12
7.5	Alternate method for determining average sphericity and roundness	13
8	Acid solubility	13
8.1	Purpose	13
8.2	Description	13
8.3	Equipment and materials	14
8.4	Procedure	14
9	Turbidity test	15
9.1	Purpose	15
9.2	Description	16
9.3	Equipment and materials	16
9.4	Equipment calibration	16

9.5	Procedure	16
10	Procedures for determining proppant bulk density, apparent density and absolute density	17
10.1	Purpose	17
10.2	Description	17
10.3	Bulk density	17
10.4	Apparent density	19
10.5	Absolute density	21
11	Proppant crush-resistance test	21
11.1	Purpose	21
11.2	Description	21
11.3	Equipment and materials	22
11.4	Sample preparation	22
11.5	Crush-resistance procedure	23
12	Loss on ignition of resin-coated proppant	25
12.1	Objective	25
12.2	Apparatus and materials	25
12.3	Loss-on-ignition procedure for whole-grain proppant	25
	Annex A (informative) Formazin solution preparation	27
	Bibliography	28