

# DIN EN ISO 13628-8:2008-02 (E)

Petroleum and natural gas industries - Design and operation of subsea production systems - Part 8: Remotely Operated Vehicle (ROV) interfaces on subsea production systems (ISO 13628-8:2002); English version EN ISO 13628-8:2006

---

## Contents

Page

Foreword .....	4
Introduction .....	5
1 Scope.....	6
2 Normative references .....	6
3 Terms, definitions and abbreviated terms .....	6
3.1 Terms and definitions .....	6
3.2 Abbreviated terms.....	7
4 Intervention philosophy and functional requirements.....	7
4.1 General .....	7
4.2 Intervention by ROV.....	8
4.3 ROV intervention task configurations .....	9
4.4 Subsea facilities system design.....	15
5 Design performance .....	18
5.1 General .....	18
5.2 Materials.....	18
5.3 Load capability .....	18
5.4 Operating force or torque.....	18
5.5 Lifting devices .....	18
5.6 Quality control.....	18
5.7 Temperature ratings .....	19
5.8 Colours and marking .....	19
6 Design considerations.....	19
6.1 General .....	19
6.2 Conceptual design .....	19
6.3 Detailed design.....	21
6.4 Desired design features .....	23
6.5 Undesirable design features .....	25
7 ROV interfaces and subsea systems .....	26
8 Operational considerations .....	29
9 Indicator systems.....	29
10 Material selection .....	30
10.1 General .....	30
10.2 Selection criteria .....	30
11 Documentation .....	30
11.1 General .....	30
11.2 Equipment design .....	31
11.3 Testing.....	31
11.4 Information feedback.....	31
12 ROV interfaces .....	31
12.1 General .....	31
12.2 Stabilization .....	31
12.3 Handles for use with manipulators .....	37
12.4 Handles for use with TDUs.....	39
12.5 Rotary (low torque) interface .....	40
12.6 Rotary (high-torque) interface .....	42
12.7 Linear (push) interface — Types A and C.....	43

<b>12.8</b>	<b>Linear (push) interface type B.....</b>	<b>46</b>
<b>12.9</b>	<b>Rotary docking .....</b>	<b>47</b>
<b>12.10</b>	<b>Hot stab hydraulic connection type A — 69,0 MPa (10 000 psi) working pressure.....</b>	<b>50</b>
<b>12.11</b>	<b>Hot stab hydraulic connection type B.....</b>	<b>51</b>
<b>12.12</b>	<b>Rotary fluid coupling.....</b>	<b>54</b>
<b>12.13</b>	<b>CCO interface.....</b>	<b>56</b>
<b>12.14</b>	<b>Lifting mandrels.....</b>	<b>62</b>
<b>12.15</b>	<b>Electrical and hydraulic jumper handling .....</b>	<b>62</b>
<b>Annex A</b>	<b>(informative) Summary of work class ROV specifications .....</b>	<b>68</b>
<b>Annex B</b>	<b>(informative) Access .....</b>	<b>69</b>
<b>Annex C</b>	<b>(informative) Manipulator operating envelopes .....</b>	<b>70</b>
<b>Annex D</b>	<b>(informative) Alternative designs for end-effectors.....</b>	<b>71</b>
<b>Annex E</b>	<b>(informative) Flowline tie-in systems .....</b>	<b>73</b>
<b>Bibliography</b>	<b>.....</b>	<b>74</b>