

DIN EN 354:2010-11 (E)

Personal fall protection equipment - Lanyards

| Contents | | Page |
|--|--|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Requirements | 5 |
| 4.1 | Design and ergonomics | 5 |
| 4.2 | Materials | 5 |
| 4.3 | Terminations | 5 |
| 4.4 | Slippage for lanyards with length adjustment device | 6 |
| 4.5 | Static strength | 6 |
| 4.6 | Dynamic strength for lanyards with a length adjustment device | 6 |
| 4.7 | Corrosion resistance | 6 |
| 4.8 | Marking and information | 6 |
| 5 | Test methods | 6 |
| 5.1 | General | 6 |
| 5.2 | Conditioning | 7 |
| 5.2.1 | General conditioning | 7 |
| 5.2.2 | Conditioning to wet and cold | 7 |
| 5.2.3 | Conditioning to very cold | 7 |
| 5.3 | Examination of design | 7 |
| 5.4 | Examination of materials | 7 |
| 5.5 | Examination of terminations | 8 |
| 5.6 | Slippage test for lanyards with a length adjustment device | 8 |
| 5.7 | Static strength test | 8 |
| 5.7.1 | Apparatus | 8 |
| 5.7.2 | Method | 8 |
| 5.7.3 | Static test for lanyard with a length adjustment device after the dynamic test | 9 |
| 5.8 | Dynamic strength test for lanyards with a length adjustment device | 9 |
| 5.8.1 | Apparatus | 9 |
| 5.8.2 | Test procedure | 10 |
| 5.9 | Corrosion resistance test | 12 |
| 6 | Marking | 12 |
| 7 | Information supplied by the manufacturer | 12 |
| 8 | Packaging | 13 |
| Annex A (informative) | Significant technical changes between this European Standard and the Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC | 16 |
| Figures | Figure 1 -- Measurement of the lanyard length | 7 |
| Figure 2 -- Example of a lanyard with more than two terminations, showing the terminations to be tested | | 9 |

| | |
|---|-----------|
| Figure 3 -- Bowline knot | 10 |
| Figure 4 -- Test lanyard | 10 |
| Figure 5 -- Dynamic strength test for lanyards with a length adjustment device | 11 |