DIN EN 354:2010-11 (E)

Personal fall protection equipment - Lanyards

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Requirements 5
4.1 Design and ergonomics 5
4.2 Materials 5
4.3 Terminations 5
4.4 Slippage for lanyards with length adjustment device 6
4.5 Static strength 6
4.6 Dynamic strength for lanyards with a length adjustment device 6
4.7 Corrosion resistance 6
4.8 Marking and information 6

5 Test methods 6
5.1 General 6
5.2 Conditioning 7
5.2.1 General conditioning 7
5.2.2 Conditioning to wet and cold 7
5.2.3 Conditioning to very cold 7
5.3 Examination of design 7
5.4 Examination of materials 7
5.5 Examination of terminations 8
5.6 Slippage test for lanyards with a length adjustment device 8
5.7 Static strength test 8
5.7.1 Apparatus 8
5.7.2 Method 8
5.7.3 Static test for lanyard with a length adjustment device after the dynamic test 9
5.8 Dynamic strength test for lanyards with a length adjustment device 9
5.8.1 Apparatus 9
5.8.2 Test procedure 10
5.9 Corrosion resistance test 12

6 Marking 12

7 Information supplied by the manufacturer 12

8 Packaging 13

Annex A (informative) Significant technical changes between this European Standard and the Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC 16

Figures Figure 1 -- Measurement of the lanyard length 7

Figure 2 -- Example of a lanyard with more than two terminations, showing the terminations to be tested 9

Figure 3 -- Bowline knot 10

Figure 4 -- Test lanyard 10

Figure 5 -- Dynamic strength test for lanyards with a length adjustment device 11