

DIN EN 812:2012-04 (E)

Industrial bump caps

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Physical requirements	7
4.1	Materials and construction	7
4.2	Cradle	7
4.3	Comfort band or sweatband	7
4.4	Retention	7
4.5	Headband/nape strap	7
4.6	Chin strap	8
4.7	Ventilation	8
4.8	Accessories	8
5	Performance requirements	8
5.1	Mandatory requirements	8
5.1.1	Impact protection	8
5.1.2	Resistance to penetration	8
5.1.3	Chin strap anchorages	8
5.2	Optional requirements	8
5.2.1	Very low temperature (-20 °C or -30 °C)	8
5.2.2	Resistance to flame	9
5.2.3	Electrical properties	9
6	Test requirements	9
6.1	Samples	9
6.2	Conditioning for testing	10
6.2.1	Temperature conditioning cabinet	10
6.2.2	Low temperature	10
6.2.3	High temperature	10
6.2.4	Water immersion	10
6.2.5	Artificial ageing	10
6.2.6	Very low temperature	11
6.3	Testing atmosphere	11
6.4	Headforms	11
6.4.1	Construction	11
6.4.2	Selection of size	11
6.5	Impact protection	11
6.5.1	Principle	11
6.5.2	Apparatus	11
6.5.3	Procedure	12
6.6	Resistance to penetration	12
6.6.1	Principle	12
6.6.2	Apparatus	12
6.6.3	Procedure	13
6.7	Chin strap anchorages	13
6.7.1	Principle	13
6.7.2	Apparatus	13

6.7.3	Procedure	13
6.8	Resistance to flame	14
6.8.1	Principle	14
6.8.2	Apparatus	14
6.8.3	Test procedure	14
6.9	Electrical properties	14
6.9.1	Test 1	14
6.9.2	Test 2	15
6.9.3	Test 3	15
7	Marking and information	15
7.1	Markings on the bump cap	15
7.2	Additional information to be supplied by the manufacturer	16
Annex A (informative) Recommendations for materials and construction		18
Annex B (informative) Alternative method for artificial ageing		19
Annex C (informative) Significant technical changes between this European Standard and Annex ZA (normative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC Personal Protective Equipment		21
Bibliography		22