DIN EN 812:2012-04 (E)

Industrial bump caps

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Physical requirements 7
4.1 Materials and construction 7
4.2 Cradle 7
4.3 Comfort band or sweatband 7
4.4 Retention 7
4.5 Headband/nape strap 7
4.6 Chin strap 8
4.7 Ventilation 8
4.8 Accessories 8

5 Performance requirements 8
5.1 Mandatory requirements 8
5.1.1 Impact protection 8
5.1.2 Resistance to penetration 8
5.1.3 Chin strap anchorages 8
5.2 Optional requirements 8
5.2.1 Very low temperature (-20 °C or -30 °C) 8
5.2.2 Resistance to flame 9
5.2.3 Electrical properties 9

6 Test requirements 9
6.1 Samples 9
6.2 Conditioning for testing 10
6.2.1 Temperature conditioning cabinet 10
6.2.2 Low temperature 10
6.2.3 High temperature 10
6.2.4 Water immersion 10
6.2.5 Artificial ageing 10
6.2.6 Very low temperature 11
6.3 Testing atmosphere 11
6.4 Headforms 11
6.4.1 Construction 11
6.4.2 Selection of size 11
6.5 Impact protection 11
6.5.1 Principle 11
6.5.2 Apparatus 11
6.5.3 Procedure 12
6.6 Resistance to penetration 12
6.6.1 Principle 12
6.6.2 Apparatus 12
6.6.3 Procedure 13
6.7 Chin strap anchorages 13
6.7.1 Principle 13
6.7.2 Apparatus 13

6.7.3 Procedure 13
6.8 Resistance to flame 14
6.8.1 Principle 14
6.8.2 Apparatus 14
6.8.3 Test procedure 14
6.9 Electrical properties 14
6.9.1 Test 1 14
6.9.2 Test 2 15
6.9.3 Test 3 15

7 Marking and information 15
7.1 Markings on the bump cap 15
7.2 Additional information to be supplied by the manufacturer 16

Annex A (informative) Recommendations for materials and construction 18

Annex B (informative) Alternative method for artificial ageing 19

Annex C (informative) Significant technical changes between this European Standard and Annex ZA (normative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC Personal Protective Equipment 21

Bibliography 22