ISO 18640-2:2018 (E)

Protective clothing for firefighters — Physiological impact — Part 2: Determination of physiological heat load caused by protective clothing worn by firefighters

Contents

Foreword

Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 Symbols and abbreviations
- 5 Evaluation method
 - 5.1 General
 - 5.2 Firefighting scenarios
 - 5.2.1 Standard scenario for THS measurements
 - 5.3 THS measurement
 - 5.3.1 General
 - 5.3.2 Apparatus and software
 - 5.3.3 Heat flux
 - 5.3.3.1 Heat flux measurement with additional temperature sensors
 - 5.3.4 Wicking layer correction
 - 5.3.5 Skin diffusion (Esk)
 - 5.3.6 Data exchange with physiological model
 - 5.3.7 Measurement control

6 Measurement

6.1 General

- 6.2 THS measurement
- 6.2.1 Test preparation
- 6.2.2 Software settings
- 6.2.3 Sampling and test specimen
- 6.2.4 Measurement procedure
- 6.2.4.1 General
- 6.2.4.2 Data acquisition
- 6.2.4.3 End of measurement
- 6.2.5 Data evaluation

7 Test report

- 7.1 General
- 7.1.1 Specimen identification
- 7.1.2 Measurement conditions
- 7.1.3 Results of THS measurement
- 7.2 Predicted physiological parameters
- 7.3 Contents of test report

Annex A (normative) Single-sector Thermo-physiological Human Simulator (THS)

- A.1 System components
- A.2 Coupling method
- A.3 Validation of THS
- A.3.1 Validation of physiological model
- A.3.2 Validation THS

- A.3.3 Limitations THS measurements
- A.4 Standardization of thermo-physiological models
- A.5 Open source models
- A.6 Requirements for physiological models suitable for THS measurements according to this document
- Annex B (informative) Example measurement protocol according to ISO 18640-2
- Annex C (informative) Scenarios for testing and limitation of system
 - C.1 Background
 - C.2 Definition of relevant scenario for a specific activity
 - C.2.1 General
 - C.2.2 Limitations of the torso system
 - C.2.3 Limitations of physiological models
 - C.3 Firefighting scenarios

Page count: 17