

ISO 18640-1:2018 (E)

Protective clothing for firefighters — Physiological impact — Part 1: Measurement of coupled heat and moisture transfer with the sweating torso

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviations
5	Apparatus
5.1	Sweating torso
5.1.1	General
5.1.2	Heated cylinder
5.1.3	Thermal guard sections
5.1.4	Heating and temperature control
5.1.5	Temperature measurement
5.1.6	Simulation of perspiration
5.1.7	Wicking layer
5.1.8	Balance torso weight
5.2	Computer, control system and data acquisition
5.2.1	General
5.2.2	Computer and measurement software
5.2.3	Control system
5.2.4	Data acquisition
5.2.5	Measurement control options
5.3	Climatic chamber
5.3.1	General
5.3.2	Climatic chamber sensors
5.4	Fan system
5.5	Sweat water supply
5.5.1	Gravimetric sweat water control system
5.6	Simulation of air layers
6	Sampling and test specimens
6.1	General
6.1.1	Size of samples
6.1.2	Type of test specimen
6.1.3	Garment/ensemble specification
6.2	Number of test specimens
7	Specimen preparation
7.1	Pre-treatment
7.2	Conditioning
8	Measurement procedure
8.1	Test preparation
8.1.1	Preparation of climatic chamber
8.1.2	Wind speed
8.2	Specimen testing
8.2.1	General

8.2.1.1	Standard phase profile
8.2.2	Dressing the torso
8.2.3	Recording specimen identification and test observations
8.2.4	Starting the test
8.2.4.1	Data acquisition
8.2.5	Calculated values
8.2.5.1	Thermal insulation: Rct (torso) (phase 1 of standard experiment)
8.2.5.2	Cooling properties (phase 2 of standard experiment)
8.2.5.3	Drying properties and post-cooling (phase 3 of standard experiment)
8.2.5.4	End of experiment, data storage
9	Test report
9.1	General
9.2	Specimen identification
9.3	Experiment conditions
9.4	Calculated results
10	Maintenance and calibration
10.1	Maintenance
10.1.1	Sweat water tank
10.1.2	Valve checks
10.2	Calibration
10.2.1	General
10.2.2	Correction value for thermal resistance, Rct0 (torso)
10.2.3	Wicking layer
10.2.4	torso temperature sensors
10.2.5	torso heating power
10.2.6	torso sweat rate
10.2.7	Environmental conditions
10.3	Experiments with a standard fabric (optional)
Annex A	(informative) torso size and materials definition
A.1	torso system
A.2	Measurement cylinder
A.3	Lower guard
A.4	Upper guard
A.5	Discs separating cylinder from guards
A.6	Water supply and nozzle distribution
A.6.1	Distribution of sweating nozzles
A.7	Temperature sensors
Annex B	(informative) Calibration
B.1	Temperature calibration
B.2	Sweat water
B.3	Heating power
Annex C	(informative) Example of data evaluation
C.1	Single layer specimen (low thermal insulation)
C.2	Multi-layer specimen (high thermal insulation)
Annex D	(informative) Sample check list
Annex E	(informative) Validation of the measurement device
E.1	General
E.2	Correlation to sweating guarded hotplate
E.3	Interlab comparison
Annex F	(informative) Example Matlab code
F.1	Cooling Delay (CD)
F.2	Initial Cooling (IC)
F.3	Sustained Cooling (SC)
F.4	Condensed moisture (cond)
F.5	Dripped off moisture (drip)
F.6	Evaporated moisture (evap)

F.7	Post cooling intensity (PCint)
F.8	Post cooling duration (PCdur)
F.9	Post cooling (PC)
F.10	Drying time (tdry)

Page count: 37