ISO 18639-4:2018 (E)

PPE ensembles for firefighters undertaking specific rescue activities — Part 4: Gloves

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Design and general requirements

- 4.1 General
- 4.2 Glove sizing
- 4.2.1 Hand dimensions
- 4.2.2 Minimum sizing
- 4.2.3 Labelling
- 4.3 Glove body length
- 4.4 Wristlet or cuff
- 4.5 Other design requirements

5 Pre-treatment, conditioning and sampling

- 5.1 Inspection
- 5.2 Testing
- 5.2.1 Specimens
- 5.2.2 Exposure surface
- 5.2.3 Interpretation criteria
- 5.3 Pre-treatments
- 5.3.1 Laundering
- 5.3.2 Conditioning
- 5.3.3 Wetting

6 Performance requirements

- 6.1 General
- 6.2 Summary of requirements and classification
- 6.3 Road traffic crash (RTC)
- 6.4 Flame resistance
- 6.5 Heat transfer (flame exposure)
- 6.6 Heat transfer (radiant exposure)
- 6.7 Heat transfer (conductive exposure)
- 6.8 Heat resistance
- 6.9 Liquid penetration resistance (optional)
- 6.10 Whole glove integrity test
- 6.11 Urban search and rescue (USAR)

7 Mechanical and other requirements

- 7.1 Abrasion resistance
- 7.2 Cut resistance
- 7.3 Tear resistance
- 7.4 Puncture resistance
- 7.5 Label legibility
- 7.6 Ergonomic requirements
- 7.6.1 Dexterity
- 7.6.2 Grip

7.6.3 Donning

8 Leather chromium(VI) content

9 Marking

10 Manufacturer/supplier information

Annex A (normative) Grip test

A.1 Principle
A.2 Equipment
A.3 Specimens
A.4 Procedure
A.5 Test report

Annex B (normative) Donning test

B.1 Principle
B.2 Specimens
B.3 Procedure
B.4 Test report

Annex C (normative) Whole glove integrity test

C.1 Principle
C.2 Equipment
C.3 Specimens
C.4 Procedure
C.5 Test report

Annex D (informative) Marking

Page count: 20