ISO 16073-9:2020 (E)

Wildland firefighting personal protective equipment — Requirements and test methods — Part 9: Firehoods

Contents

Foreword

Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 General design requirements
 - 4.1 General
 - 4.2 Firehood flexibility and facial opening
 - 4.3 Yoke interface area
 - 4.4 Sizing
 - 4.5 Seam construction
 - 4.6 Labels
 - 4.7 Particulate protection (Optional)
- 5 Sampling and pre-treatment
 - 5.1 Sampling
 - 5.2 Pre-treatment by cleaning
 - 5.3 Conditioning

6 Performance requirements

- 6.1 Flame resistance Face ignition
- 6.2 Sewing thread thermal stability
- 6.3 Heat resistance
- 6.4 Heat transfer Flame exposure
- 6.5 Heat transfer Radiant exposure
- 6.6 Residual burst strength of material following radiant heat exposure
- 6.7 Seam burst strength
- 6.8 Dimensional change
- 6.9 Particulate protection
- 6.9.1 General
- 6.9.2 Test method 1
- 6.9.3 Test method 2
- 6.10 Water vapour resistance
- 7 Marking and labelling
 - 7.1 General
 - 7.2 Label durability and legibility
 - 7.3 Compliance marking requirements
- 8 Information supplied by the manufacturer
- Annex A (normative) Donning, doffing and shape retention test
- Annex B (normative) Particulate test method 1
 - B.1 Introduction
 - B.2 Principle
 - B.3 Test equipment
 - B.4 Procedure

- B.5 Calculation of the penetration
- Annex C (normative) Particulate test method 2
 - C.1 Introduction
 - Apparatus and test parameters Procedure C.2
 - C.3
 - C.4 Calculation of the penetration
- Annex D (informative) Particulate testing results

Page count: 16