

ISO 5725-3:1994-12 (E)

Accuracy (trueness and precision) of measurement methods and results - Part 3: Intermediate measures of the precision of a standard measurement method

Contents	Page
1 Scope	1
2 Normative references	2
3 Definitions	2
4 General requirement	2
5 Important factors	2
6 Statistical model	3
6.1 Basic model	3
6.2 General mean, m	3
6.3 Term B	4
6.4 Terms B_0 , $B_{(1)}$, $B_{(2)}$, etc.	4
6.5 Error term, e	5
7 Choice of measurement conditions	5
8 Within-laboratory study and analysis of intermediate precision measures	6
8.1 Simplest approach	6
8.2 An alternative method	6
8.3 Effect of the measurement conditions on the final quoted result	7
9 Interlaboratory study and analysis of intermediate precision measures	7
9.1 Underlying assumptions	7
9.2 Simplest approach	7
9.3 Nested experiments	7
9.4 Fully-nested experiment	8
9.5 Staggered-nested experiment	9
9.6 Allocation of factors in a nested experimental design	9
9.7 Comparison of the nested design with the procedure given in ISO 5725-2	9
9.8 Comparison of fully-nested and staggered-nested experimental designs	9
Annexes	
A Symbols and abbreviations used in ISO 5725	10
B Analysis of variance for fully-nested experiments	12
B.1 Three-factor fully-nested experiment	12
B.2 Four-factor fully-nested experiment	13
C Analysis of variance for staggered-nested experiments	15
C.1 Three-factor staggered-nested experiment	15
C.2 Four-factor staggered-nested experiment	16
C.3 Five-factor staggered-nested experiment	17
C.4 Six-factor staggered-nested experiment	18
D Examples of the statistical analysis of intermediate precision experiments	19
D.1 Example 1 - Obtaining the [time + operator]-different intermediate precision standard deviation, $s_{(TO)}$, within a specific laboratory at a particular level of the test	19
D.2 Example 2 - Obtaining the time-different intermediate precision standard deviation by interlaboratory experiment	20
E Bibliography	25