

# ISO 11843-6:2019 (E)

## Capability of detection — Part 6: Methodology for the determination of the critical value and the minimum detectable value in Poisson distributed measurements by normal approximations

---

### Contents

|         |   |
|---------|---|
|         | Foreword  |
|         | Introduction  |
| 1       | Scope   |
| 2       | Normative references  |
| 3       | Terms and definitions   |
| 4       | Measurement system and data handling  |
| 5       | Computation by approximation  |
| 5.1     | The critical value based on the normal distribution   |
| 5.2     | Determination of the critical value of the response variable  |
| 5.3     | Sufficient capability of the detection criterion  |
| 5.4     | Confirmation of the sufficient capability of detection criterion  |
| 6       | Reporting the results from an assessment of the capability of detection   |
| 7       | Reporting the results from an application of the method   |
| Annex A | (informative) Symbols used in this document   |
| Annex B | (informative) Estimating the mean value and variance when the Poisson distribution is approximated by the normal distribution |
| Annex C | (informative) An accuracy of approximations   |
| Annex D | (informative) Selecting the number of channels for the detector   |
| Annex E | (informative) Examples of calculations  |
| E.1     | Example 1: Measurement of hazardous substances by X-ray diffractometry (XRD)  |
| E.1.1   | Statistical analysis  |
| E.1.2   | Estimating the minimum detectable concentration of asbestos   |
| E.2     | Example 2: Measurement of contamination on the surface of silicon wafers by X-ray photoelectron spectroscopy (XPS)            |
| E.2.1   | Statistical analysis  |
| E.2.2   | Estimating the minimum detectable concentration of hydrocarbon by the approximation   |

Page count: 23