

# ISO 11843-2:2000-05 (E)

## Capability of detection - Part 2: Methodology in the linear calibration case

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Experimental design .....</b>	<b>2</b>
<b>4.1</b>	<b>General .....</b>	<b>2</b>
<b>4.2</b>	<b>Choice of reference states .....</b>	<b>2</b>
<b>4.3</b>	<b>Choice of the number of reference states, I, and the (numbers of) replications of procedure, J, K and L .....</b>	<b>3</b>
<b>5</b>	<b>The critical values <math>y_c</math> and <math>x_c</math> and the minimum detectable value <math>x_d</math> of a measurement series .....</b>	<b>3</b>
<b>5.1</b>	<b>Basic assumptions .....</b>	<b>3</b>
<b>5.2</b>	<b>Case 1 -- Constant standard deviation .....</b>	<b>4</b>
<b>5.3</b>	<b>Case 2 -- Standard deviation linearly dependent on the net state variable .....</b>	<b>6</b>
<b>6</b>	<b>Minimum detectable value of the measurement method .....</b>	<b>9</b>
<b>7</b>	<b>Reporting and use of results .....</b>	<b>10</b>
<b>7.1</b>	<b>Critical values .....</b>	<b>10</b>
<b>7.2</b>	<b>Minimum detectable values .....</b>	<b>10</b>
	<b>Annex A (normative) Symbols and abbreviations .....</b>	<b>11</b>
	<b>Annex B (informative) Derivation of formulae .....</b>	<b>14</b>
	<b>Annex C (informative) Examples .....</b>	<b>20</b>
	<b>Bibliography .....</b>	<b>24</b>