

ISO 11843-2:2000-05 (E)

Capability of detection - Part 2: Methodology in the linear calibration case

| Contents | | Page |
|-----------------|--|-------------|
| | Foreword | iv |
| | Introduction | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Experimental design | 2 |
| 4.1 | General | 2 |
| 4.2 | Choice of reference states | 2 |
| 4.3 | Choice of the number of reference states, I, and the (numbers of) replications of procedure, J, K and L | 3 |
| 5 | The critical values y_c and x_c and the minimum detectable value x_d of a measurement series | 3 |
| 5.1 | Basic assumptions | 3 |
| 5.2 | Case 1 -- Constant standard deviation | 4 |
| 5.3 | Case 2 -- Standard deviation linearly dependent on the net state variable | 6 |
| 6 | Minimum detectable value of the measurement method | 9 |
| 7 | Reporting and use of results | 10 |
| 7.1 | Critical values | 10 |
| 7.2 | Minimum detectable values | 10 |
| | Annex A (normative) Symbols and abbreviations | 11 |
| | Annex B (informative) Derivation of formulae | 14 |
| | Annex C (informative) Examples | 20 |
| | Bibliography | 24 |