

ISO/TR 11843-8:2021-11 (E)

Capability of detection - Part 8: Guidance for the implementation of the ISO 11843 series

Contents		Page
Foreword		iv
0	Introduction	v
1	Scope	1
2	Normative references	1
3	Terms, definitions and symbols	1
3.1	Terms and definitions	1
3.2	Symbols	1
4	Historical survey of terms	3
5	Fundamental concepts of detection limit (minimum detectable value in ISO 11843)	4
5.1	General	4
5.2	General definition of detection limit	4
5.3	Detection limit with probability	5
5.4	Detection limit with probabilities and	6
6	Pragmatic view of and	9
6.1	Statistical definitions of and	9
6.2	Actual examples of and values	9
7	In-depth explanations and examples of the Parts in the ISO 11843 series	9
7.1	General	9
7.2	ISO 11843-3 and ISO 11843-4	10
7.2.1	General	10
7.2.2	Number of repeated measurements, J and K	10
7.2.3	Determination of the minimum detectable value	11
7.2.4	Confirmation of the minimum detectable value for an obtained experimental value with the number of repeated measurements, N	11
7.2.5	Number of repeated measurements, J and K, in ISO 11843-5 and ISO 11843-7	13
7.3	ISO 11843-6	13
7.3.1	Overview of ISO 11843-6	13
7.3.2	Features of pulse count measurement	13
7.4	Example from ISO 11843-7	19
Annex A (informative)	Standard normal random variable	23
Annex B (informative)	Difference between the power of test and the minimum detectable value	25
Annex C (informative)	Calculation example from ISO 11843-4	27
Annex D (informative)	Calculation example from ISO 11843-6:2019, Annex E (Measurement of hazardous substances by X-ray diffractometer)	28
Annex E (informative)	Comparison between the Poisson exact arithmetic and the approximations ..	31
Annex F (informative)	Association of IUPAC recommended detection limit with the ISO 11843 series	36
Bibliography		38