

# ISO 3951-1:2022-08 (E)

## Sampling procedures for inspection by variables - Part 1: Specification for single sampling plans indexed by acceptance quality limit (AQL) for lot-by-lot inspection for a single quality characteristic and a single AQL

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Symbols .....</b>	<b>6</b>
<b>5</b>	<b>Choice of a sampling plan .....</b>	<b>7</b>
5.1	Choice between variables and attributes .....	7
5.2	General .....	8
5.3	Choice between the s-method and -method .....	8
5.4	Choice of inspection level and AQL .....	9
<b>6</b>	<b>Standard procedures for the s-method .....</b>	<b>10</b>
6.1	General .....	10
6.2	Single specification limits .....	10
6.3	Double specification limits .....	11
<b>7</b>	<b>Standard procedures for the -method .....</b>	<b>11</b>
7.1	General .....	11
7.2	Single specification limits .....	11
7.3	Double specification limits .....	12
<b>8</b>	<b>The p*-method .....</b>	<b>12</b>
<b>9</b>	<b>Switching between inspection severities .....</b>	<b>13</b>
9.1	Rules for switching between inspection severities .....	14
9.2	Records for switching between inspection severities .....	15
<b>10</b>	<b>Relation to ISO 2859-1 .....</b>	<b>15</b>
10.1	Similarities .....	15
10.2	Differences .....	16
<b>11</b>	<b>Allowing for measurement uncertainty .....</b>	<b>17</b>
<b>12</b>	<b>Normality, data transformations and outliers .....</b>	<b>17</b>
12.1	Normality .....	17
12.2	Data transformations .....	17
12.3	Outliers .....	18
<b>13</b>	<b>Monitoring and recording of inspection results .....</b>	<b>18</b>
13.1	Monitoring of inspection results .....	18
13.2	Process capability and performance assessment .....	18
13.3	Monitoring of process parameters .....	18

<b>14</b>	<b>Tables .....</b>	<b>19</b>
<b>14.1</b>	<b>Form k for single sampling plans: s-method .....</b>	<b>19</b>
<b>14.2</b>	<b>Form k for single sampling plans: -method .....</b>	<b>26</b>
<b>14.3</b>	<b>Form p* single sampling plans .....</b>	<b>33</b>
<b>14.4</b>	<b>Values of f for maximum process standard deviation (MPSD) .....</b>	<b>40</b>
<b>14.5</b>	<b>Supplementary acceptance constants for qualifying towards reduced inspection .....</b>	<b>40</b>
<b>15</b>	<b>Examples .....</b>	<b>41</b>
<b>15.1</b>	<b>General .....</b>	<b>41</b>
<b>15.2</b>	<b>Examples for the s-method .....</b>	<b>41</b>
<b>15.3</b>	<b>Examples for the -method .....</b>	<b>48</b>
<b>15.4</b>	<b>Examples for the p*-method .....</b>	<b>52</b>
<b>Annex A (informative) Procedures for obtaining s and .....</b>		<b>55</b>
<b>Annex B (informative) Accommodating measurement variability .....</b>		<b>58</b>
<b>Annex C (informative) Sampling strategies .....</b>		<b>63</b>
<b>Annex D (informative) Operating characteristics for the -method .....</b>		<b>65</b>
<b>Annex E (informative) Operating characteristic for the s-method - tabulated values for single sampling plans, normal inspection .....</b>		<b>66</b>
<b>Annex F (informative) Consumer's risk qualities .....</b>		<b>75</b>
<b>Annex G (informative) Producer's risks .....</b>		<b>82</b>
<b>Annex H (informative) Construction of acceptance diagrams for double specification limits .....</b>		<b>90</b>
<b>Annex I (informative) Use of the underlying software .....</b>		<b>101</b>
<b>Bibliography .....</b>		<b>106</b>