ISO 3951-3:2007-05 (E)

Sampling procedures for inspection by variables - Part 3: Double sampl ing schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 2

3 Terms and definitions 2

4 Symbols and abbreviations 7

5 Acceptance quality limit (AQL) 9

6 Switching rules for normal, tightened and reduced inspection 10

7 Relation to ISO 2859-1 10

8 Limiting quality protection 11

9 Planning 12

10 Choice between variables and attributes 12

11 Choice of method 13

12 Choice between single and double sampling plans 13

13 Choice of inspection level and AQL 14

14 Choice of sampling scheme 14

15 Preliminary operations 15

16 Standard univariate "s" method procedures 16

17 Standard univariate "" method procedures 25

18 Procedure during continuing inspection 32

19 Normality and outliers 32

20 Records 32

21 Operation of switching rules 33

22 Discontinuation and resumption of inspection 33

23 Switching between the "s" and " " methods 34

Annex A (informative) Standard multivariate "s" method procedures for double sampling with independent quality characteristics 72

Annex B (informative) Standard multivariate "" method procedures for double sampling with independent quality characteristics 74

Annex C (informative) Standard multivariate combined "s" and "" method procedures for double sampling with independent quality characteristics 76

Annex D (informative) Location of text on key features 78

Annex E (normative) Estimating the process fraction nonconforming 81

Annex F (informative) Form k "s" method single sampling plans matched to the corresponding single sampling plans by attributes 87

Annex G (informative) Form k "" method single sampling plans matched to the corresponding single sampling plans by attributes 91

Annex H (informative) Average sample sizes for double sampling by variables: "s" method 95

Annex I (informative) Producer's risks for the "s" method 98

Annex J (informative) Tabulated operating characteristics for double sampling plans with known process standard deviation 100

Annex K (informative) Ratios of ASSIs of double sampling plans under normal inspection to the sample size of the corresponding single sampling plan by variables 107

Annex L (informative) Ratios of the ASSIs of double sampling plans by variables to the ASSIs of corresponding plans by attributes 109

Annex M (informative) Design methodology 112

Bibliography 113