DIN EN 818-3:2008-12 (E)

Short link chain for lifting purposes - Safety - Part 3: Medium tolerance chain for chain slings - Grade 4 (includes Amendment A1:2008)

Contents

Page

Foreword 4

Introduction 5

1 Scope 5

2 Normative references 5

3 Terms and definitions 6

4 Hazards 6

5 Safety requirements 7
5.1 General 7
5.2 Dimensions 7
5.2.1 Nominal size of chain, dn 7
5.2.2 Tolerance on material diameter (except at the weld) 7
5.2.3 Weld diameter 7
5.2.4 Length dimensionally affected by welding 7
5.2.5 Pitch and widths 7
5.3 Materials and heat treatment 9
5.3.1 !!!!General 9
5.3.2 Quality of material 9
5.3.3 Heat treatment 10
5.3.4 !!!!Stainless steel 10
5.4 Mechanical properties 10
5.4.1 Manufacturing proof force (MPF) 10
5.4.2 Breaking force (BF) and total ultimate elongation (A) 10
5.4.3 Bend deflection 10

6 Verification of safety requirements 11
6.1 Qualification of personnel 11
6.2 Size of lot and selection of samples 12
6.3 Manufacturing proof force, breaking force and total ultimate elongation 12
6.3.1 Static tensile test 12
6.3.2 Manufacturing proof force acceptance criteria 12
6.3.3 Breaking force and total ultimate elongation acceptance criteria 12
6.4 Bend deflection 12
6.4.1 Bend test 12
6.4.2 Bend deflection acceptance criteria 13

7 Marking 13

8 Manufacturer's certificate 13

9 !!!!Information""""" for use 13

Annex A (informative) Calculation of dimensions, working load limits and mechanical properties 14

A.1 Dimensions and tolerances 14
A.2 Working load limits and mechanical properties 14

Annex B (informative) Mass of chain 17

Annex C (informative) Designation system for chain (medium tolerance) - Grade 4 18

Annex ZA (informative) !!!!Relationship between this European Standard and the Essential Requirements of EU Directive 98/37/EC 19

Annex ZB (informative) !!!!Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC 20

!!!!Bibliography 21