Toughness of chain steels

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Types of chain and extraction of specimens 2

4 Materials, chemical composition and heat-treatment 2

5 Tensile tests on chains 2

6 Conventional tensile tests on standard specimens 3

7 Notch impact tests 3

8 Fracture mechanics tests on notched chain links with slits 4

9 Fracture mechanics tests on notched three-point bend specimens with slits and fatigue cracks 6

10 Correlation between the load-bearing capacity of chain links containing slits and material toughness 7

11 Fracture mechanics derivation of chain links 7

12 Load-bearing and brittle fracture transition concept — Requirements 8

13 Correlation of test results with data from the literature 9

14 Summary 9

Figure 1 — Results C_V tests: Standard specimen (EN 10045) 11

Figure 2 — Load-time diagram for instrumented C_V 13

Figure 3 — Crack arrest load as function of temperature 14

Figure 4 — Noncrystalline area in C_V — Test 15

Figure 5 — Load–COD diagram for TPB specimens with fatigue crack and eroded slits material type T, T = –40 °C 16

Figure 6 — Load–COD diagram for TPB specimens with fatigue crack and eroded slits material grade VH, T = –40 °C 17

Figure 7 — Comparison of pre-cracked and eroded chain link material grade VH, T = –40 °C 18

Figure 8 —Chain link specimen 19

Figure 9 — Clip gauge fixed in chain link 20

Figure 10 — Calibration of clip gauge for COD measurement 21

Figure 11 — Test specimen at –40 °C, three links 21

Figure 12 — Effect of slit size on loadability of chain, T = –40 °C 22

Figure 13 — Load–COD diagram for tension tests on chains with eroded slit, T = –40 °C, a/d = 0,22 23

Figure 14 — Load–COD diagram for tension tests on chains with eroded slit, T = –40 °C, a/d = 0,43 24

Figure 15 — Load–COD diagram for tension tests on chains with eroded slit, T = –40 °C, a/d = 0,64 25

Figure 16 — Stable crack growth chain Type T, a/d = 0,22 — Marked by heat tinting 26

Figure 17 — Effect of slit size on absorbed energy of chains, T = –40 °C 27

Figure 18 — Fracture mechanics tests on TPB specimens **28**
Figure 19 — Fracture mechanics concepts **29**
Figure 20 — Fracture toughness values for TPB specimens with eroded slits, T = –40 °C, a/w = 0,5 ..... **30**
Figure 21 — R-curves material Type T, T = –40 °C, a/w = 0,4 ..... **31**
Figure 22 — R-curves material Type T, T = –40 °C, a/w = 0,4 ..... **32**
Figure 23 — Nominal fracture stress in chain link, correlated with fracture mechanics properties **33**
Figure 24 — Nominal fracture stress in chain link correlated with fracture mechanics properties **34**
Figure 25 — Correlation of fracture load and C_V **toughness** **35**
Figure 26 — Correlation nominal fracture stress of chain and C_V **toughness** **36**
Figure 27 — Finite element analysis of chain links with eroded slit, a/d = 0 ..... **37**
Figure 28 — Finite element analysis of chain links with eroded slit, a/d = 0,22 ..... **37**
Figure 29 — Finite element analysis of chain links with eroded slit, a/d = 0,64 ..... **38**
Figure 30 — Nominal stresses in cracked chain link **39**
Figure 31 — Correction factor for long bending bars [5] **40**
Figure 32 — Stress intensity factor for long bending bars **41**
Figure 33 — Safety relations between requirement and service conditions **42**
Figure 34 — Nominal fracture stress in chain link, correlated with fracture mechanics properties **43**
Figure 35 — Correlation nominal fracture stress of chain and C_V **toughness** **44**
Figure 36 — Correlation of fracture and C_V **toughness pre-cracked TPB specimens** **45**
Table 1 — Chemical composition of the chain steels **46**
Table 2 — Tensile test results on chain specimens (5 links) **46**
Table 3 — Tensile test results on standard specimens (EN 10002, B6*30) T = –40 °C **46**
Table 4 — Results of C_V **tests** **47**
Table 5 — Crack arrest loads of C_V **tests** **47**
Table 6 — Noncrystalline area of C_V **specimens** **47**
Table 7 — Transition behaviour of chain materials **47**
Table 8 — Maximum loads of chain-tests at –40 °C **48**
Table 9 — Maximum displacement for chain tests, T = –40 °C **48**
Table 10 — Absorbed energy of the chain tests, T = –40 °C **48**
Table 11 — Evaluation of fracture mechanics test on TPB specimens **49**
Table 12 — Fracture mechanics tests on TPB specimens with eroded slits **49**
Table 13 — Fracture mechanics tests on TPB specimens with fatigue cracks, T = –40 °C **49**
Table 14 — R curves data material Type T **50**
Table 15 — Calculation of K_Q **values for chain grade VH** **50**
Bibliography **51**