

# ISO 6185-4:2011-07 (E)

## Inflatable boats - Part 4: Boats with a hull length of between 8 m and 24 m with a motor power rating of 15 kW and greater

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	3
4	Symbols .....	4
5	Materials .....	5
5.1	General .....	5
5.2	Materials making up the buoyancy tube .....	5
5.3	Wood .....	7
5.4	Metal parts .....	7
5.5	Glass-reinforced plastics .....	7
5.6	Other materials .....	7
5.7	Buoyant material used in foam-filled buoyancy tubes .....	7
6	Functional components .....	9
6.1	Conditioning .....	9
6.2	Buoyancy tube and hull fittings (items bonded to the buoyancy tube) .....	9
6.3	Valves (if applicable) .....	9
6.4	Transom .....	10
6.5	Hull interior drainage .....	10
6.6	Remote steering system (where offered as standard or optional equipment) .....	10
6.7	Towing, anchoring and mooring strong points .....	10
6.8	Seating and attachment systems (where offered as standard or optional equipment) .....	10
6.9	Electrical installations (where offered as standard or optional equipment) .....	11
6.10	Engine and engine spaces .....	11
6.11	Ventilation of petrol motor and petrol tank compartments (where applicable) .....	11
6.12	Devices for lifting the boat (if applicable) .....	11
6.13	Fire protection (if applicable) .....	11
6.14	Openings in hull, deck or superstructure .....	11
6.15	Gas systems .....	11
6.16	Navigation lights .....	12
6.17	Discharge prevention .....	12
6.18	Noise emissions (applicable to inboard engines installations without integral exhaust) ....	12
7	Safety requirements of the completed boat .....	12
7.1	Maximum permissible number of persons (crew limit) .....	12
7.2	Motor power calculation .....	12
7.3	Maximal manoeuvring speed (if applicable) .....	12
7.4	Static stability of the boat .....	15
7.5	Maximum load capacity .....	16
7.6	Buoyancy requirements .....	16
7.7	Compartmentation (inflatable buoyancy tubes) .....	17
7.8	Nominal pressures (inflatable buoyancy tubes) .....	18
7.9	Strength of the inflatable buoyancy tube .....	18

<b>7.10</b>	<b>Man overboard prevention and recovery .....</b>	<b>19</b>
<b>7.11</b>	<b>Field of vision from the helm position .....</b>	<b>19</b>
<b>7.12</b>	<b>Provision for a liferaft or liferafts .....</b>	<b>19</b>
<b>7.13</b>	<b>Self-bailing .....</b>	<b>19</b>
<b>7.14</b>	<b>Buoyancy tube attachment strength test (type test only) .....</b>	<b>20</b>
<b>7.15</b>	<b>Strength of the rigid structure (type test only) .....</b>	<b>22</b>
<b>7.16</b>	<b>Strength of principal factory-fitted accessories .....</b>	<b>22</b>
<b>8</b>	<b>Builder's plate(s) .....</b>	<b>23</b>
<b>9</b>	<b>Owner's manual .....</b>	<b>24</b>
<b>10</b>	<b>Standard equipment .....</b>	<b>24</b>
	<b>Annex A (informative) Typical Type IX powered boat .....</b>	<b>25</b>
	<b>Annex B (informative) Typical Type X powered boat .....</b>	<b>26</b>
	<b>Bibliography .....</b>	<b>27</b>