

DIN 86210-1:2012-07 (E)

Replenishment with operating materials and disposal of fluid waste from seagoing vessels - Part 1: Hose fittings for hose assemblies up to PN 10

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Requirements	6
4.1	General	6
4.2	Permissible operating pressures and temperatures	7
4.3	Resistance of coupling materials to various media	7
4.4	Description of a dry disconnect coupling	7
4.5	Description of a full-flow coupling	7
5	Overview	8
5.1	General	8
5.2	Principle of on-board connection (ship)	9
5.3	Principle of shoreside/barge-side connection	9
5.4	Using hoses and types of hose fitting	12
6	Couplings	12
6.1	Coupling applications	12
6.2	Interface of the couplings	12
7	Materials	19
8	Supply media	19
8.1	Diesel fuels	19
8.2	Heavy fuels	20
8.3	Lubricants	20
8.4	Fresh water	20
9	Discharge media	21
9.1	Fuel sludge	21
9.2	Waste oil	21
9.3	Wastewater (bilge water, greywater and blackwater)	21
Annex A (informative) Type testing		23
A.1	Type testing	23
A.2	Maintenance	24
Figure 1 -- Principle of on-board connection (ship)		9
Figure 2 -- Connection by means of a hose assembly and crane		10
Figure 3 -- Connection by means of a hose assembly and hinged/swivelling pipe		11
Figure 4 -- Interface geometry of dry disconnect coupling		13

Figure 5 -- Seal geometry of dry disconnect coupling	15
Figure 6 -- Side elevation, dry disconnect coupling	17
Figure 7 -- Mechanical coding of dry disconnect couplings (only for DN 25)	18
Figure A.1 -- Testing coupling seals	25
Figure A.2 -- Testing the coupling	26
Tables Table 1 -- Allocation of nominal diameters to specific media	12
Table 2 -- Coupling dimensions	14
Table 3 -- Seal dimensions	16
Table 4 -- Coding of dry disconnect couplings	18