

ISO 12217-3:2013-03 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 3: Boats of hull length less than 6 m

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	2
3	Terms and definitions	2
3.1	Primary	2
3.2	Downflooding	4
3.3	Condition and mass	5
3.4	Other definitions	7
4	Symbols	9
5	Procedure	10
5.1	Maximum load	10
5.2	Sailing or non-sailing	10
5.3	Tests to be applied	10
5.4	Alternatives	11
5.5	Variation in input parameters	11
6	Tests to be applied to non-sailing boats	11
6.1	General	11
6.2	Habitable non-sailing multihull boats	11
6.3	Downflooding	12
6.4	Recess size	17
6.5	Offset-load test	19
6.6	Heel due to wind action	26
6.7	Level flotation test	26
6.8	Basic flotation test	27
6.9	Capsize-recovery test	27
6.10	Detection and removal of water	28
7	Tests to be applied to sailing boats	28
7.1	General	28
7.2	Downflooding	29
7.3	Recess size	29
7.4	Flotation tests	29
7.5	Capsize-recovery test	30
7.6	Knockdown recovery test	31
7.7	Wind stiffness test	32
7.8	Inverted buoyancy	34
8	Safety signs	35
9	Application	35
9.1	Deciding the design category	35
9.2	Meaning of the design categories	35

Annex A (normative) Full method for required downflooding height	37
Annex B (normative) Methods for calculating downflooding angle	40
Annex C (normative) Method for flotation tests	42
Annex D (normative) Flotation material and elements	47
Annex E (normative) Calculation method for basic flotation requirement	49
Annex F (normative) Information for owner's manual	51
Annex G (informative) Summary of requirements	55
Annex H (informative) Worksheets	57
Bibliography	74