

DIN EN ISO 18854:2015-08 (E)

Small craft - Reciprocating internal combustion engines exhaust emission measurement - Test-bed measurement of gaseous and particulate exhaust emissions (ISO 18854:2015)

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | 6 |
| Introduction | | 7 |
| 1 | Scope | 8 |
| 2 | Normative references | 8 |
| 3 | Terms and definitions | 8 |
| 4 | Symbols and abbreviations | 10 |
| 4.1 | General symbols | 10 |
| 4.2 | Symbols for fuel composition | 12 |
| 4.3 | Symbols and abbreviations for the chemical components | 12 |
| 4.4 | Abbreviations | 13 |
| 5 | Test conditions | 14 |
| 5.1 | Engine test conditions | 14 |
| 5.1.1 | Test condition parameter | 14 |
| 5.1.2 | Test validity | 14 |
| 5.2 | Engines with charge air cooling | 14 |
| 5.3 | Power | 15 |
| 5.4 | Specific test conditions | 15 |
| 5.4.1 | Engine air inlet system | 15 |
| 5.4.2 | Engine exhaust system | 15 |
| 5.4.3 | Cooling system | 15 |
| 5.4.4 | Lubricating oil | 16 |
| 5.4.5 | Adjustable carburetors | 16 |
| 5.4.6 | Crankcase breather | 16 |
| 6 | Test fuels | 16 |
| 7 | Application of the engine family concept and choice of parent engine | 16 |
| 8 | Measurement equipment and data to be measured | 17 |
| 8.1 | General | 17 |
| 8.2 | Dynamometer specification | 17 |
| 8.3 | Exhaust gas flow | 17 |
| 8.3.1 | General | 17 |
| 8.3.2 | Direct measurement method | 17 |
| 8.3.3 | Air and fuel measurement method | 18 |
| 8.3.4 | Fuel flow and carbon balance method | 18 |
| 8.3.5 | Tracer measurement method | 18 |
| 8.3.6 | Air flow and air-to-fuel ratio measurement method | 19 |
| 8.3.7 | Total dilute exhaust gas flow | 20 |
| 8.4 | Accuracy | 20 |
| 8.5 | Determination of the gaseous components | 21 |
| 8.5.1 | General analyser specifications | 21 |
| 8.5.2 | Gas drying | 22 |

| | | |
|--------|--|----|
| 8.5.3 | Analysers | 22 |
| 8.5.4 | Sampling for gaseous emissions | 24 |
| 8.6 | Particulate determination | 25 |
| 8.6.1 | General | 25 |
| 8.6.2 | Particulate sampling filters | 26 |
| 8.6.3 | Weighing chamber and analytical balance specifications | 27 |
| 9 | Calibration of the analytical instruments | 27 |
| 9.1 | General requirements | 27 |
| 9.2 | Calibration gases | 28 |
| 9.2.1 | General | 28 |
| 9.2.2 | Pure gas | 28 |
| 9.2.3 | Calibration and span gases | 28 |
| 9.2.4 | Use of gas dividers | 28 |
| 9.2.5 | Oxygen interference gases | 29 |
| 9.3 | Operating procedure for analysers and sampling system | 29 |
| 9.4 | Leakage test | 29 |
| 9.5 | Calibration procedure | 29 |
| 9.5.1 | Instrument assembly | 29 |
| 9.5.2 | Warm-up time | 29 |
| 9.5.3 | NDIR and HFID analyser | 29 |
| 9.5.4 | GC and HPCL | 30 |
| 9.5.5 | Establishment of the calibration curve | 30 |
| 9.5.6 | Alternative calibration methods | 30 |
| 9.5.7 | Verification of the calibration | 30 |
| 9.6 | Calibration of tracer gas analyser for exhaust flow measurement | 30 |
| 9.7 | Efficiency test of the NO _x converter | 31 |
| 9.7.1 | General | 31 |
| 9.7.2 | Test setup | 31 |
| 9.7.3 | Calibration | 31 |
| 9.7.4 | Calculation | 32 |
| 9.7.5 | Adding of oxygen.25 | 32 |
| 9.7.6 | Activation of the ozonator | 32 |
| 9.7.7 | NO _x mode | 32 |
| 9.7.8 | Deactivation of the ozonator | 32 |
| 9.7.9 | NO mode | 32 |
| 9.7.10 | Test interval | 32 |
| 9.7.11 | Efficiency requirement | 32 |
| 9.8 | Adjustment of the FID | 33 |
| 9.8.1 | Optimization of the detector response | 33 |
| 9.8.2 | Hydrocarbon response factors | 33 |
| 9.8.3 | Oxygen interference check | 33 |
| 9.8.4 | Efficiency of the Non-Methane Cutter (NMC) | 34 |
| 9.8.5 | Methanol response factor | 35 |
| 9.9 | Interference effects with CO, CO ₂ , NO _x , O ₂ , NH ₃ , and N ₂ O analysers | 35 |
| 9.9.1 | General | 35 |
| 9.9.2 | CO analyser interference check | 36 |
| 9.9.3 | NO _x analyser quench checks | 36 |
| 9.9.4 | O ₂ analyser interference | 37 |
| 9.9.5 | Cross-interference check compensation for NH ₃ and N ₂ O measurement channels using IR and UV measurement techniques | 38 |
| 9.10 | Calibration intervals | 41 |
| 10 | Calibration of the particulate measuring system | 41 |
| 10.1 | General | 41 |
| 10.2 | Calibration procedure | 41 |
| 10.2.1 | Flow measurement | 41 |
| 10.2.2 | Exhaust gas analysers | 41 |
| 10.2.3 | Carbon flow check | 41 |
| 10.3 | Checking the partial-flow conditions | 41 |
| 10.4 | Calibration intervals | 41 |
| 11 | Calibration of the CVS full-flow dilution system | 41 |

| | | |
|--------|--|----|
| 11.1 | General | 41 |
| 11.2 | Calibration of the Positive Displacement Pump (PDP) | 41 |
| 11.2.1 | General | 41 |
| 11.2.2 | Data analysis | 41 |
| 11.3 | Calibration of the Critical-Flow Venturi (CFV) | 42 |
| 11.3.1 | General | 42 |
| 11.3.2 | Data analysis | 42 |
| 11.4 | Calibration of the Subsonic Venturi (SSV) | 43 |
| 11.4.1 | General | 43 |
| 11.4.2 | Data analysis | 43 |
| 11.5 | Total system verification | 44 |
| 11.5.1 | General | 44 |
| 11.5.2 | Metering with a critical flow orifice | 44 |
| 11.5.3 | Metering by means of a gravimetric technique | 44 |
| 12 | Test cycles (running conditions) | 45 |
| 12.1 | Requirements | 45 |
| 12.2 | Test cycles | 45 |
| 12.2.1 | Applications | 45 |
| 12.2.2 | Test modes and weighting factors | 46 |
| 12.2.3 | Performing the test | 47 |
| 13 | Test run | 47 |
| 13.1 | Preparation of the sampling filters | 47 |
| 13.2 | Installation of the measuring equipment | 47 |
| 13.3 | Starting the dilution system and the engine | 47 |
| 13.4 | Adjustment of the dilution ratio | 47 |
| 13.5 | Determination of test points | 48 |
| 13.6 | Checking of the analysers | 48 |
| 13.7 | Test cycles | 48 |
| 13.7.1 | Test sequence | 48 |
| 13.7.2 | Analyser response | 49 |
| 13.7.3 | Particulate sampling | 49 |
| 13.7.4 | Engine conditions | 49 |
| 13.8 | Re-checking the analysers | 49 |
| 13.9 | Test report | 49 |
| 14 | Data evaluation for gaseous and particulate emissions | 49 |
| 14.1 | Gaseous emissions | 49 |
| 14.2 | Particulate emissions | 50 |
| 15 | Calculation of the gaseous emissions | 50 |
| 15.1 | General | 50 |
| 15.2 | Determination of the exhaust gas flow | 51 |
| 15.3 | Dry/wet correction | 51 |
| 15.4 | NO _x correction for humidity and temperature | 53 |
| 15.5 | Calculation of the emission mass flow rates | 54 |
| 15.5.1 | Raw exhaust gas | 54 |
| 15.5.2 | Dilute exhaust gas | 55 |
| 15.5.3 | Determination of the NMHC concentration | 57 |
| 15.6 | Calculation of the specific emission | 58 |
| 16 | Calculation of the particulate emission | 58 |
| 16.1 | Particulate correction factor for humidity | 58 |
| 16.2 | Partial-flow dilution system | 59 |
| 16.2.1 | Isokinetic systems | 59 |
| 16.2.2 | Systems with measurement of CO ₂ or NO _x concentration | 59 |
| 16.2.3 | Systems with CO ₂ measurement and carbon balance method | 59 |
| 16.2.4 | Systems with flow measurement | 60 |
| 16.3 | Full-flow dilution system | 60 |
| 16.4 | Calculation of the particulate mass flow rate | 60 |
| 16.5 | Calculation of the specific emissions | 61 |

| | | |
|--|--|----|
| 16.6 | Effective weighting factor | 61 |
| 17 | Determination of the gaseous emissions | 62 |
| 17.1 | General | 62 |
| 17.2 | Main exhaust components CO, CO ₂ , HC, NO _x , O ₂ | 62 |
| 17.3 | Ammonia analysis | 67 |
| 17.4 | Methane analysis | 68 |
| 17.4.1 | Gas chromatographic (GC) method (Figure 6) | 68 |
| 17.4.2 | Non-methane cutter (NMC) method (Figure 7) | 70 |
| 17.5 | Methanol analysis | 71 |
| 17.6 | Formaldehyde analysis | 72 |
| 18 | Determination of the particulates | 74 |
| 18.1 | General | 74 |
| 18.2 | Dilution system | 74 |
| 18.2.1 | Partial-flow dilution system (Figures 10 to 18) | 74 |
| 18.2.2 | Full-flow dilution system | 86 |
| 18.3 | Particulate sampling system | 89 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2013/53/EC | | 93 |
| Bibliography | | 94 |