

ISO 6218:2015-09 (E)

Inland navigation vessels - Manually- and power-operated coupling devices for pushing on its and coupled vessels - Safety requirements and main dimensions

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Safety requirements	2
4.1	General	2
4.1.1	Components	2
4.1.2	Requirements	4
4.2	Limitation of actuating power for power operated coupling devices	5
4.3	Limitation of rope speed	5
4.4	Strength requirements	5
5	Models	5
5.1	Operation	5
5.2	Position of handwheel/motor	5
5.3	With or without tensioning device	6
6	Design	6
6.1	Rope drum	6
6.1.1	Drum capacity	6
6.1.2	Drum diameter	6
6.1.3	Rope fastening	6
6.2	Handwheel	6
6.2.1	Clearances	6
6.2.2	Construction	6
6.2.3	Handhold	6
6.3	Power-driven equipment	7
6.4	Combined operating modes	7
6.5	Arresting device	7
6.5.1	General	7
6.5.2	Arresting devices for manually operated coupling devices	7
6.5.3	Arresting devices for power-driven coupling devices	7
6.6	Protective device	7
6.7	Footbrakes for manually operated coupling devices	7
6.8	Brakes for power operated coupling devices	7
6.9	Gears	8
6.10	Tensioning device for manually operated coupling systems	8
6.11	Change gear for manually operated coupling devices	8
6.12	Foundation	8
6.13	Guide track	8
7	Dimensions and characteristic values	8
7.1	General	8
7.2	Characteristic values	8
7.3	Main dimensions of the coupling device	9
7.3.1	Manually operated coupling devices	9
7.3.2	Power operated coupling devices	11

7.4	Arrangement of foundation	12
8	Material	12
9	Operating instructions and assembly instructions	13
9.1	General	13
9.2	Assembly instructions	13
9.3	Operating instructions	13
10	Designation	13
11	Marking	14
	Annex A (normative) Individual and type testing	15
	Bibliography	16