

ISO 8666:2016-07 (E)

Small craft - Principal data

Contents		Page
Foreword		v
1	Scope	1
2	Terms and definitions	1
3	Symbols, designations and units	2
4	Measurements	3
4.1	General	3
4.2	Longitudinal	4
4.2.1	General	4
4.2.2	Maximum length, L_{max}	4
4.2.3	Length of the hull, LH	4
4.2.4	Waterline length, LWL	7
4.3	Athwartship	8
4.3.1	General	8
4.3.2	Maximum beam, B_{max}	8
4.3.3	Beam of hull, BH	8
4.3.4	Beam, waterline, BWL	8
4.3.5	Maximum beam, waterline, BWL_{max}	8
4.3.6	Beam between hull centers, BCB	8
4.4	Vertical	9
4.4.1	Maximum depth, D_{max}	9
4.4.2	Midship depth, $DLWL/2$	9
4.4.3	Freeboard, F	10
4.4.4	Draught, T	10
4.4.5	Draught, air, H_a	10
4.4.6	Headroom	11
4.5	Other data	11
4.5.1	Deadrise angle,	11
4.5.2	Reference sail area, AS	12
4.5.3	Standard sail area, A'S	12
4.5.4	Windage area, A_{lv}	12
4.5.5	Volume of the craft, V	12
5	Masses	13
5.1	Mass, net shipping, mN	13
5.2	Mass, gross shipping, mG	13
5.3	Mass, light craft, mLC	14
5.3.1	Items of equipment included in mLC	14
5.3.2	Items of equipment and other items not included in mLC	15
5.4	Performance test mass, mP	15
5.5	Mass of the craft when towed on a trailer, mT	16
5.5.1	General	16
5.5.2	Items of equipment included in mT	16
5.5.3	Items of equipment not included in mT	18
5.5.4	Exclusions, inclusions	18
5.6	Maximum load, mML	18
6	Loading conditions	19
6.1	Test condition	19

6.2	Ready-for-use condition	19
6.3	Fully loaded ready-for-use condition	19
6.4	Empty craft condition	19
6.5	Light craft condition	20
6.6	Minimum operating condition	21
6.7	Loaded arrival condition	21
6.8	Maximum load condition	21
7	Tolerances	21
7.1	Published data	21
7.2	Preliminary specification	22
7.3	Reference lengths	22
	Bibliography	23