ISO 18154:2017-03 (E)

Ships and marine technology - Safety valve for cargo tanks of LNG carriers - Design and testing requirements

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Main valve components 2
4.1 Body 2
4.2 Nozzle 2
4.3 Disk 2
4.4 Cover 2
4.5 Diaphragm 2

5 Design 3

6 Materials 4

7 Production testing and inspection 4
7.1 Purpose 4
7.2 Impact test 4
7.3 Non-destructive inspection 4
7.4 Pressure test 5
7.4.1 General requirement 5
7.4.2 Fluid 5
7.4.3 Duration 5
7.4.4 Test equipment 5
7.5 Surface inspection 5
7.6 Visual inspection 5

8 Performance test 6
8.1 Performance test in ambient temperature 6
8.1.1 Purpose 6
8.1.2 Number of test times 6
8.1.3 Fluid 6
8.1.4 Acceptance criteria 6
8.2 Leakage test in ambient temperature 6
8.2.1 Purpose 6
8.2.2 Fluid 6
8.2.3 Test pressure 6
8.2.4 Duration 6
8.2.5 Acceptance leakage rate 6
8.2.6 Test equipment 7
8.3 Performance test in low temperature 7
8.3.1 Purpose 7
8.3.2 Number of test times 7
8.3.3 Fluid 7
8.3.4 Acceptance criteria 7
8.4 Preparation for the performance test in low temperature 7
8.4.1 Start temperature for the test 7

8.4.2 Safety requirement 7
8.4.3 Test system 7
8.5 Leakage test in low temperature 8
8.5.1 Purpose 8
8.5.2 Fluid 8
8.5.3 Test pressure 8
8.5.4 Duration 8
8.5.5 Acceptance tolerance 9
8.5.6 Test equipment 9

9 Vacuum test 9
9.1 Purpose 9
9.2 Vacuum condition 9
9.2.1 Test temperature 9
9.2.2 Vacuum set test 9
9.2.3 Number of test times 9
9.2.4 Fluid 9

10 Type test 9

11 Determination of pilot operated safety valve performance 9

12 Sizing of pilot operated safety valves 10

13 Marking and sealing 10

Bibliography 11