

ISO 20155:2017-08 (E)

Ships and marine technology - Test method of flow induced in-pipe noise source characteristics for a ship-used pump

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Two-port source model and test method of source characteristic of pump	2
4.1 Two-port source model of a pump	2
4.2 Test methods for source characteristic parameters of the pump	3
5 Test rig	4
5.1 Test loop	4
5.2 Installation of test pump	5
5.3 Ground foundation and supporting structure	6
5.4 Test-bed pipeline	6
5.5 Test section	6
5.6 Throttling valve	6
5.7 Secondary acoustic exciter	7
5.8 Water tank	7
6 Instrumentation	7
6.1 General	7
6.2 Static measurements	7
6.3 Dynamic measurements	7
7 Test preparation	8
8 Test procedure	8
9 Data processing	9
9.1 General	9
9.2 Passive characteristic of noise source	9
9.3 Active characteristic	9
10 Evaluation criteria for the test result	9
11 Test report	10
11.1 Overview	10
11.2 General information	10
11.3 Test record	11
11.4 Test result	11
Annex A (informative) Theoretical models of a two-port source and transformation mutually between matrix Z, S, T	13
Annex B (informative) Evaluation of quantities at inlet and outlet ports	15

Annex C (informative) Judgment of effectiveness for the test	17
Annex D (informative) Formulae for determining passive characteristics of noise source	19
Annex E (informative) Formulae for determining active characteristics of source	20
Annex F (informative) Verification of test method taking a T-shaped sound excitor as a two- port acoustic source	21
Bibliography	24