

ISO 20313:2018-01 (E)

Ships and marine technology - Cathodic protection of ships

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Competence of personnel	3
5	Design basis	3
5.1	General	3
5.2	Cathodic protection criteria	4
5.3	Design process	5
5.4	Design considerations	6
5.4.1	Cathodic protection zones of ship hull (external)	6
5.4.2	Internal cathodic protection zones	6
5.4.3	Component characteristics	7
5.4.4	Service conditions	7
5.5	Current demand	7
5.5.1	General	7
5.5.2	Design current density for bare steel	8
5.5.3	Design current density for coated steel	8
5.5.4	Current demand	9
5.6	Cathodic protection systems	11
5.7	Electrical continuity	12
5.8	Fitting out period	12
6	Impressed current system	12
6.1	Objectives	12
6.2	Design considerations	12
6.3	Equipment considerations	13
6.3.1	Power source, monitoring and control systems	13
6.3.2	Anodes	15
6.3.3	Dielectric shields	16
6.3.4	Permanent reference and measurement electrodes	16
6.3.5	Cables and terminations	16
6.3.6	Cofferdams	17
7	Galvanic anode systems	17
7.1	Objectives	17
7.2	Design considerations	18
7.3	Anode materials	18
7.4	Factors determining the anode current output and operating life	19
7.5	Location of anodes	19
7.5.1	External hull surfaces	19
7.5.2	Internal surfaces	20
8	Commissioning, operation and maintenance	23
8.1	Objectives	23

8.2	Measurement procedures	23
8.3	Commissioning: Galvanic systems	24
8.4	Commissioning: Impressed current systems	24
8.4.1	Visual inspection	24
8.4.2	Pre-energizing measurements	25
8.4.3	Initial energizing	25
8.4.4	Performance assessment	25
8.5	Operation and maintenance	26
8.5.1	General	26
8.5.2	Galvanic anode systems	26
8.5.3	Impressed current systems	26
8.5.4	Interaction with adjacent structures	27
8.6	Dry-docking period	27
9	The protection of ships' hulls during fitting out and when laid up	28
9.1	Fitting out period	28
9.2	Lay-up period	28
10	Documentation	28
10.1	Objectives	28
10.2	Galvanic anode systems	29
10.3	Impressed current system	29
Annex A (informative) Impressed current system for external hulls of ships based on two cathodic protection zones		31
Annex B (informative) Guidance on design current density values for cathodic protection of ship's hulls and tanks		32
Annex C (informative) Anode resistance, current and life duration formulae		34
Annex D (informative) Electrical bonding systems		39
Annex E (informative) Monitoring of electrical bonding of a ship's propeller		41
Annex F (informative) Impressed current system for ships based on an aft (stern) system only		42
Annex G (informative) Location of galvanic anodes in the stern area		43
Annex H (informative) Electrochemical characteristics of impressed current anodes		44
Annex I (informative) Cofferdam arrangements		46
Annex J (informative) Cathodic protection of a moored ship using suspended galvanic anodes		49
Annex K (informative) Anode/cathode separation (dielectric shield) calculations		51
Annex L (Informative) Galvanic anode specifications		52
Annex M (informative) Use of portable coupons		55
Bibliography		56