

ISO 20313:2018-01 (E)

Ships and marine technology - Cathodic protection of ships

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Competence of personnel | 3 |
| 5 | Design basis | 3 |
| 5.1 | General | 3 |
| 5.2 | Cathodic protection criteria | 4 |
| 5.3 | Design process | 5 |
| 5.4 | Design considerations | 6 |
| 5.4.1 | Cathodic protection zones of ship hull (external) | 6 |
| 5.4.2 | Internal cathodic protection zones | 6 |
| 5.4.3 | Component characteristics | 7 |
| 5.4.4 | Service conditions | 7 |
| 5.5 | Current demand | 7 |
| 5.5.1 | General | 7 |
| 5.5.2 | Design current density for bare steel | 8 |
| 5.5.3 | Design current density for coated steel | 8 |
| 5.5.4 | Current demand | 9 |
| 5.6 | Cathodic protection systems | 11 |
| 5.7 | Electrical continuity | 12 |
| 5.8 | Fitting out period | 12 |
| 6 | Impressed current system | 12 |
| 6.1 | Objectives | 12 |
| 6.2 | Design considerations | 12 |
| 6.3 | Equipment considerations | 13 |
| 6.3.1 | Power source, monitoring and control systems | 13 |
| 6.3.2 | Anodes | 15 |
| 6.3.3 | Dielectric shields | 16 |
| 6.3.4 | Permanent reference and measurement electrodes | 16 |
| 6.3.5 | Cables and terminations | 16 |
| 6.3.6 | Cofferdams | 17 |
| 7 | Galvanic anode systems | 17 |
| 7.1 | Objectives | 17 |
| 7.2 | Design considerations | 18 |
| 7.3 | Anode materials | 18 |
| 7.4 | Factors determining the anode current output and operating life | 19 |
| 7.5 | Location of anodes | 19 |
| 7.5.1 | External hull surfaces | 19 |
| 7.5.2 | Internal surfaces | 20 |
| 8 | Commissioning, operation and maintenance | 23 |
| 8.1 | Objectives | 23 |

| | | |
|---|--|----|
| 8.2 | Measurement procedures | 23 |
| 8.3 | Commissioning: Galvanic systems | 24 |
| 8.4 | Commissioning: Impressed current systems | 24 |
| 8.4.1 | Visual inspection | 24 |
| 8.4.2 | Pre-energizing measurements | 25 |
| 8.4.3 | Initial energizing | 25 |
| 8.4.4 | Performance assessment | 25 |
| 8.5 | Operation and maintenance | 26 |
| 8.5.1 | General | 26 |
| 8.5.2 | Galvanic anode systems | 26 |
| 8.5.3 | Impressed current systems | 26 |
| 8.5.4 | Interaction with adjacent structures | 27 |
| 8.6 | Dry-docking period | 27 |
| 9 | The protection of ships' hulls during fitting out and when laid up | 28 |
| 9.1 | Fitting out period | 28 |
| 9.2 | Lay-up period | 28 |
| 10 | Documentation | 28 |
| 10.1 | Objectives | 28 |
| 10.2 | Galvanic anode systems | 29 |
| 10.3 | Impressed current system | 29 |
| Annex A (informative) Impressed current system for external hulls of ships based on two cathodic protection zones | | 31 |
| Annex B (informative) Guidance on design current density values for cathodic protection of ship's hulls and tanks | | 32 |
| Annex C (informative) Anode resistance, current and life duration formulae | | 34 |
| Annex D (informative) Electrical bonding systems | | 39 |
| Annex E (informative) Monitoring of electrical bonding of a ship's propeller | | 41 |
| Annex F (informative) Impressed current system for ships based on an aft (stern) system only | | 42 |
| Annex G (informative) Location of galvanic anodes in the stern area | | 43 |
| Annex H (informative) Electrochemical characteristics of impressed current anodes | | 44 |
| Annex I (informative) Cofferdam arrangements | | 46 |
| Annex J (informative) Cathodic protection of a moored ship using suspended galvanic anodes | | 49 |
| Annex K (informative) Anode/cathode separation (dielectric shield) calculations | | 51 |
| Annex L (Informative) Galvanic anode specifications | | 52 |
| Annex M (informative) Use of portable coupons | | 55 |
| Bibliography | | 56 |