DIN EN ISO 12215-5:2019-06 (E)

Small craft - Hull construction and scantlings - Part 5: De sign pressures for monohulls, design stresses, scantlings determination (ISO 12215-5:2008, including Amd 1:2014)

Contents

Page

European foreword ... 6

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Directive 2013/53/EU aimed to be covered ... 7

Foreword ... 8

Foreword to Amendment ... 9

Introduction ... 10

1 Scope ... 11

2 Normative references ... 11

3 Terms and definitions ... 12

4 Symbols ... 14

5 General ... 16

6 Dimensions, data and areas ... 17
6.1 Dimensions and data ... 17
6.2 Areas ... 17
6.2.1 General ... 17
6.2.2 Bottom areas ... 17
6.2.3 Side areas ... 18
6.2.4 Decks and superstructures ... 18
6.2.5 Panel fully in one area or across two areas ... 19

7 Pressure adjusting factors ... 19
7.1 General ... 19
7.2 Design category factor k_{DC} ... 19
7.3 Dynamic load factor n_{CG} ... 19
7.3.1 General ... 19
7.3.2 Dynamic load factor n_{CG} for planing motor craft in planing mode ... 20
7.3.3 Dynamic load factor n_{CG} for sailing craft and displacement motor craft ... 20
7.4 Longitudinal pressure distribution factor k_L ... 20
7.5 Area pressure reduction factor k_{AR} ... 21
7.5.1 General ... 21
7.5.2 Maximum value of k_{AR} ... 22
7.5.3 Minimum values of k_{AR} ... 22
7.6 Hull side pressure reduction factor k_Z ... 22
7.7 Superstructure and deckhouse pressure reduction factor k_{SUP} ... 23
7.8 Light and stable sailing craft pressure correcting factor for slamming k_{SLS} ... 23

8 Design pressures ... 24
8.1 Motor craft design pressure ... 24
8.1.1 General ... 24
8.1.2 Motor craft bottom pressure in displacement mode P_{BMD} ... 24
8.1.3 Motor craft bottom pressure in planing mode P_{BMP} ... 24
8.1.4 Motor craft side pressure in displacement mode P_{SMD} ... 25
8.1.5 Motor craft side pressure in planing mode P_{SMP} ... 25
8.1.6 Motor craft deck pressure P_{DM} ... 25
8.1.7 Motor craft pressure for superstructures and deckhouses $P_{SUP\ M}$ ... 25

8.2 Sailing craft design pressure 26
8.2.1 Sailing craft bottom pressure 26
8.2.2 Sailing craft side pressure P_{SS} 26
8.2.3 Sailing craft deck pressure P_{DS} 26
8.2.4 Sailing craft superstructure pressure $P_{SUP\ S}$ 26
8.3 Watertight bulkheads and integral tank boundaries design pressure 26
8.3.1 Watertight bulkheads pressure P_{WB} 26
8.3.2 Integral tank bulkheads and boundaries P_{TB} 27
8.3.3 Wash plates 28
8.3.4 Collision bulkheads 28
8.3.5 Non-watertight or partial bulkheads 28
8.3.6 Transmission of pillar loads 28
8.4 Design pressures for structural components where k_{AR} would be $\leq 0{,}25$ 28

9 Dimensions of panels and stiffeners 29
9.1 Dimensions of plating panels 29
9.1.1 Short dimension of the panel b 29
9.1.2 Large dimension of the panel l 29
9.1.3 Non-rectangular panels 30
9.1.4 Large panel assessment when there are no or few stiffeners 31
9.1.5 Panels between hard chines 33
9.1.6 Characteristics of natural stiffeners 33
9.2 Dimensions of stiffeners 33
9.2.1 Spacing of stiffeners s 33
9.2.2 Long dimension of a stiffener l_u (unsupported length) 33
9.2.3 Redundant stiffeners 35

10 Plating — Scantling equations 35
10.1 Thickness adjustment factors for plating 35
10.1.1 Bending deflection factor k_1 for sandwich plating 35
10.1.2 Panel aspect ratio factor for strength k_2 and for stiffness k_3 36
10.1.3 Curvature correction factor k_C for curved plates 36
10.1.4 Final design pressure and panel analysis 37
10.1.5 Shear force and bending moment on a panel 37
10.2 FRP single-skin plating 38
10.2.1 Design stress for FRP single-skin plating 38
10.2.2 Required thickness for FRP single-skin plating 38
10.2.3 Use of bulking material 38
10.3 Metal plating — Aluminium alloy and steel 39
10.3.1 Design stress for metal plating 39
10.3.2 Required thickness for metal plating 40
10.4 Laminated wood or plywood single-skin plating 40
10.4.1 Design stress for laminated wood or plywood plating 40
10.4.2 Required thickness for laminated wood or plywood plating 41
10.5 FRP sandwich plating 41
10.5.1 General 41
10.5.2 Design stress for sandwich plating 41
10.5.3 Minimum section modulus and second moment 42
10.5.4 Thickness required by shear load capabilities 43
10.5.5 Minimum core shear strength 44
10.5.6 Minimum sandwich skin fibre mass requirements 45
10.6 Single-skin plating minimum thickness 45
10.6.1 General 45
10.6.2 Minimum thickness or mass of reinforcement for the hull 46
10.6.3 Minimum deck thickness 46

11 Stiffening members requirements 46
11.1 General 46
11.2 Properties adjustment factors for stiffeners 47

11.2.1 Curvature factor for stiffeners k_{CS} 47
11.2.2 Stiffener shear area factor k_{SA} 47
11.3 Design stresses for stiffeners 47
11.4 Requirements for stiffeners made with similar materials 48
11.4.1 For any material: minimum section modulus and shear area 48
11.4.2 Supplementary stiffness requirements for FRP 48
11.5 Requirements for stiffeners made with dissimilar materials 49
11.6 Effective plating 50
11.7 Overall dimensions of stiffeners 51
11.7.1 Geometry 51
11.7.2 Maximum proportions between dimensions within a stiffener 51
11.7.3 Connection between the stiffener and the plating 53
11.8 Structural bulkheads 53
11.8.1 Plywood bulkheads 53
11.8.2 Sandwich bulkheads 53
11.8.3 Metal bulkheads 54
11.9 Structural support for sailing craft ballast keel 54

12 Owner's manual 54
12.1 General 54
12.2 Normal mode of operation 54
12.3 Possibility of outer skin damage 54

Annex A (normative) Simplified method for scantling determination 55
A.1 Alternative method for sailing craft of categories C and D of $L_H < 9$ m 55
A.1.1 General 55
A.1.2 Determination of panel laminate thickness 55
A.2 Correction for other materials 56
A.2.1 General 56
A.2.2 E glass-based GRP materials 56
A.2.3 Correction for sandwich construction 57
A.2.4 Correction for metal and wood 58

Annex B (normative) Drop test for boats of < 6 m 59
B.1 Theoretical background 59
B.1.1 Theory of drop test 59
B.1.2 Wave conditions 59
B.1.3 Relative impact speed 59
B.1.4 Verification of "drop height" 60
B.1.5 Safety margin 60
B.1.6 Fatigue 60
B.2 Test and compliance 60
B.2.1 General 60
B.2.2 Practical test 60
B.2.3 Inspection and compliance requirements 61

Annex C (normative) FRP laminates properties and calculations 62
C.1 Methods for the determination of mechanical properties 62
C.1.1 General 62
C.1.2 Evaluation level method "EL-a" 62
C.1.3 Evaluation level method "EL-b" 64
C.1.4 Evaluation level method "EL-c" 64
C.1.5 Builders' responsibilities 65
C.2 Default mechanical properties 65
C.2.1 Status of default equations 65
C.2.2 Default values for glass-based composites 66
C.2.3 Comments on calculated Tables C.4 b) and C.5 b) 67
C.2.4 Carbon-based composites 68
C.2.5 Aramid-based composites 69

C.2.6 Values for double bias or quadraxial laminates 70
C.3 Examples 71
C.3.1 Fibre mass by direct measurement 71
C.3.2 Overall fibre content by mass by calculation 71
C.3.3 Fibre content by mass for non-glass fibre from Table C.2 72
C.3.4 Flexural properties of non-glass laminates 72
C.3.5 Flexural strength of mixed spray-up CSM and WR 72

Annex D (normative) Sandwich mechanical core properties and sandwich calculation 73
D.1 Sandwich core material mechanical properties 73
D.1.1 General 73
D.1.2 Tested core material mechanical properties 73
D.1.3 Non-tested core material properties 73
D.2 Sandwich equations 75
D.2.1 General 75
D.2.2 Equations for general sandwich sections (see Figure D.1) 76
D.2.3 Approximations 76
D.2.4 Equations for symmetrical sandwich 76
D.3 Sandwich pre-calculated tables and figures 77

Annex E (normative) Wood laminate properties and wood calculations 79
E.1 Wood laminates 79
E.1.1 General 79
E.1.2 Plywood 79
E.1.3 Moulded in-situ veneers 80
E.1.4 Strip planking 80
E.2 Wood laminate mechanical properties 81
E.2.1 Tested properties 81
E.2.2 Non-tested properties 81
E.3 Laminated wood calculation examples 86

Annex F (normative) Mechanical properties of metals 88

Annex G (normative) Geometric properties of stiffeners 90
G.1 General 90
G.2 Glass-reinforced plastic 90
G.2.1 General 90
G.2.2 “Squat” former top hats 90
G.2.3 “Square” former top hats 92
G.2.4 “Tall” former top hats 94
G.3 Round bilges and hard chines 96
G.4 Metal hull stiffeners 97
G.5 Wood stiffeners 99
G.5.1 General 99
G.5.2 Wood stiffeners pre-calculated tables 99
G.5.3 General method for assessing wood stiffeners 103
G.5.4 Analysis of wooden stiffeners 104
G.5.5 Worked example 105

Annex H (normative) Laminate stack analysis 107
H.1 General 107
H.1.1 Application 107
H.1.2 Strip or panel analysis 107
H.2 Strip analysis 108
H.2.1 Calculation of the parameters for a multilayer laminate (see Table H.2) 108
H.3 Method for stiffeners 114
H.3.1 General 114
H.3.2 Worked example 115

Bibliography 118