DIN EN ISO 12215-8:2019-09 (E)

Small craft - Hull construction and scantlings - Part 8: Rudders (ISO 12215-8:2009 , including Cor 1:2010)

Contents

Page

European foreword 5

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Directive 2013/53/EU aimed to be covered 6

Foreword 7

Introduction 8

1 Scope 9

2 Normative references 9

3 Terms and definitions 9

4 Symbols 10

5 Design stresses 12
5.1 Rudder material 12

6 Rudder and steering arrangement, rudder types 13
6.1 General 13
6.1.1 General definition 13
6.1.2 Multi-rudder arrangement 13
6.1.3 Vertical support 13
6.1.4 Hard over stops 13
6.1.5 Actuating system of the rudder 14
6.1.6 Emergency tiller 14
6.2 Rudder types 14
6.2.1 Type I (spade) rudders (see Figures 1 and 2) 14
6.2.2 Rudder spade with trapezoidal shape 15
6.2.3 Rudder types II to V (see Figure 3) 17

7 Design rudder force calculation 18
7.1 General 18
7.2 Force F_1 and corresponding load case 19
7.3 Force F_2 and corresponding load case 20

8 Rudder bending moment and reactions at bearings 21
8.1 General 21
8.2 Analysis of spade rudder (Type I) 21
8.2.1 Values of k_b, bending moment M and reactions at bearings for spade rudders (Type I) 21
8.3 Analysis of skeg rudders (Types II to V) 22
8.3.1 General 22
8.3.2 Methods of calculation 22
8.3.3 Continuous beam theory 22
8.3.4 Simplified method 22

9 Rudder design torque, T 24

10 Rudder and rudder stock design 25
10.1 Load bearing parts of the rudder 25
10.2 Metal rudder stock material 25

10.3 Design stress for metal rudder stock 26
10.4 Required diameter for solid circular metal rudder stocks 26
10.5 Vertical variation of the diameter of a Type I rudder (spade) 26
10.6 Round tubular stocks 27
10.7 Non-circular metal rudder stocks 28
10.8 Simple non-isotropic rudder stocks (e.g. wood or FRP) 29
10.8.1 Blade acting both as rudder and rudder stock 29
10.8.2 Stress requirements for wood or plywood rudders 29
10.9 Complex structural rudders and rudder stocks in composite 29
10.10 Check of deflection of Type I rudder stocks between bearings 29
11 Equivalent diameter at the level of notches 30
12 Rudder bearings, pintles and gudgeons 30
12.1 Bearing arrangement 30
12.2 Clearance between stock and bearings 31
13 Rudder stock structure and rudder construction 32
13.1 Rudder stock structure 32
13.2 Rudder construction 32
13.3 FRP rudder blades 32
13.3.1 Blades with a core 32
13.3.2 Blade skins without internal core 33
13.4 Non-FRP rudder blades 33
14 Skeg structure 33
14.1 General 33
14.2 Design stress 33
Annex A (normative) Metal for rudder stock 34
Annex B (normative) Complex composite rudder stock design 38
Annex C (normative) Complete calculation for rudders with skeg 40
Annex D (informative) Geometrical properties of some typical rudder blade shapes 44
Annex E (informative) Vertical variation of diameter for Type I rudders 47
Annex F (informative) Type I rudders — Deflection of stock between bearings 49
Bibliography 52

Tables

Table 1 — Symbols, coefficients, parameters 11
Table 2 — Values of design stresses 12
Table 3 — Calculated values of k_b for a trapezoidal spade as a function of c_2/c_1 15
Table 4 — Rudder types and effective areas 17
Table 5 — Values of r and r_{min} according to rudder type 25
Table 6 — Equivalent diameter d 28
Table 7 — Computed recommended values of diametric clearance $D - d$ between stock and bushing 31
Table A.1 — Values of σ_d for metallic rudder stocks 36
Table A.2 — Equivalence between stainless steel standard denominations 37

Table D.1 — Values of k_f and k_{f1} for typical planform shapes **45**
Table E.1 — Computed values for $\alpha = 1$, $\alpha = 0{,}75$ and $\alpha = 0{,}5$ **48**
Table F.1 — Computed maximum values of h_u/d ratio and of h_u for $30 < d < 120$ mm **51**

Figures

Figure 1 — Graphical determination of centroid, CS, of a trapeze **15**
Figure 2 — Spade rudders: Type I **16**
Figure 3 — Other rudder types: Types II to V **18**
Figure 4 — Idealization for simplified method **23**
Figure 5 — Variation of d/d_{max} as a function of h_{in}/h_u or h_{ou}/h_r **27**
Figure 6 — Determination of equivalent diameter at the level of key notches or square section **30**
Figure C.1 — Rudder with a partial skeg **42**
Figure C.2 — Rudder with a full skeg **43**
Figure D.1 — Sketch of solid and hollowed rectangular or streamlined sections **44**