

DIN EN ISO 12215-8:2019-09 (E)

Small craft - Hull construction and scantlings - Part 8: Rudders (ISO 12215-8:2009 , including Cor 1:2010)

Contents	Page
European foreword.....	5
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Directive 2013/53/EU aimed to be covered	6
Foreword	7
Introduction	8
1 Scope	9
2 Normative references.....	9
3 Terms and definitions	9
4 Symbols.....	10
5 Design stresses.....	12
5.1 Rudder material	12
6 Rudder and steering arrangement, rudder types	13
6.1 General.....	13
6.1.1 General definition.....	13
6.1.2 Multi-rudder arrangement.....	13
6.1.3 Vertical support.....	13
6.1.4 Hard over stops.....	13
6.1.5 Actuating system of the rudder.....	14
6.1.6 Emergency tiller	14
6.2 Rudder types.....	14
6.2.1 Type I (spade) rudders (see Figures 1 and 2).....	14
6.2.2 Rudder spade with trapezoidal shape.....	15
6.2.3 Rudder types II to V (see Figure 3)	17
7 Design rudder force calculation	18
7.1 General.....	18
7.2 Force F_1 and corresponding load case	19
7.3 Force F_2 and corresponding load case	20
8 Rudder bending moment and reactions at bearings.....	21
8.1 General.....	21
8.2 Analysis of spade rudder (Type I).....	21
8.2.1 Values of k_b, bending moment M and reactions at bearings for spade rudders (Type I).....	21
8.3 Analysis of skeg rudders (Types II to V)	22
8.3.1 General.....	22
8.3.2 Methods of calculation	22
8.3.3 Continuous beam theory	22
8.3.4 Simplified method.....	22
9 Rudder design torque, T.....	24
10 Rudder and rudder stock design.....	25
10.1 Load bearing parts of the rudder	25
10.2 Metal rudder stock material	25

10.3	Design stress for metal rudder stock	26
10.4	Required diameter for solid circular metal rudder stocks	26
10.5	Vertical variation of the diameter of a Type I rudder (spade)	26
10.6	Round tubular stocks	27
10.7	Non-circular metal rudder stocks.....	28
10.8	Simple non-isotropic rudder stocks (e.g. wood or FRP).....	29
10.8.1	Blade acting both as rudder and rudder stock	29
10.8.2	Stress requirements for wood or plywood rudders.....	29
10.9	Complex structural rudders and rudder stocks in composite	29
10.10	Check of deflection of Type I rudder stocks between bearings	29
11	Equivalent diameter at the level of notches.....	30
12	Rudder bearings, pintles and gudgeons	30
12.1	Bearing arrangement.....	30
12.2	Clearance between stock and bearings	31
13	Rudder stock structure and rudder construction.....	32
13.1	Rudder stock structure.....	32
13.2	Rudder construction.....	32
13.3	FRP rudder blades.....	32
13.3.1	Blades with a core.....	32
13.3.2	Blade skins without internal core	33
13.4	Non-FRP rudder blades	33
14	Skeg structure	33
14.1	General	33
14.2	Design stress.....	33
Annex A (normative)	Metal for rudder stock.....	34
Annex B (normative)	Complex composite rudder stock design	38
Annex C (normative)	Complete calculation for rudders with skeg.....	40
Annex D (informative)	Geometrical properties of some typical rudder blade shapes	44
Annex E (informative)	Vertical variation of diameter for Type I rudders.....	47
Annex F (informative)	Type I rudders — Deflection of stock between bearings	49
Bibliography	52

Tables

Table 1	— Symbols, coefficients, parameters	11
Table 2	— Values of design stresses.....	12
Table 3	— Calculated values of k_b for a trapezoidal spade as a function of c_2/c_1	15
Table 4	— Rudder types and effective areas.....	17
Table 5	— Values of r and r_{\min} according to rudder type	25
Table 6	— Equivalent diameter d	28
Table 7	— Computed recommended values of diametric clearance $D - d$ between stock and bushing	31
Table A.1	— Values of σ_d for metallic rudder stocks	36
Table A.2	— Equivalence between stainless steel standard denominations	37

Table D.1 — Values of k_f and k_{f1} for typical planform shapes.....	45
Table E.1 — Computed values for $\alpha = 1$, $\alpha = 0,75$ and $\alpha = 0,5$	48
Table F.1 — Computed maximum values of h_u/d ratio and of h_u for $30 < d < 120$ mm	51

Figures

Figure 1 — Graphical determination of centroid, CS, of a trapeze	15
Figure 2 — Spade rudders: Type I.....	16
Figure 3 — Other rudder types: Types II to V.....	18
Figure 4 — Idealization for simplified method	23
Figure 5 — Variation of d/d_{max} as a function of h_{in}/h_u or h_{ou}/h_r	27
Figure 6 — Determination of equivalent diameter at the level of key notches or square section.....	30
Figure C.1 — Rudder with a partial skeg.....	42
Figure C.2 — Rudder with a full skeg	43
Figure D.1 — Sketch of solid and hollowed rectangular or streamlined sections	44