

ISO 18692-1:2018 (E)

Fibre ropes for offshore stationkeeping — Part 1: General specification

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Materials
4.1	Rope core material
4.1.1	Fibre tenacity
4.1.2	Marine grade
4.2	Rope cover material
4.3	Other materials
5	Requirements — Rope properties
5.1	Minimum breaking strength
5.2	Minimum core tenacity
5.3	Dynamic stiffness at end of bedding-in
5.4	Torque properties
5.4.1	Torque-neutral rope
5.4.2	Torque-matched rope
5.5	Cyclic loading performance
5.6	Particle ingress protection
6	Requirements — Rope layout and construction
6.1	General
6.2	Type of construction
6.3	Rope core
6.4	Protective cover
6.5	Terminations
6.6	Length of rope
7	Rope testing
7.1	Type test
7.1.1	General
7.1.2	Sampling and testing
7.1.3	Breaking strength, core tenacity and stiffness tests
7.1.4	Torque properties tests
7.1.5	Linear density test
7.1.6	Cyclic loading endurance test
7.1.7	Protective cover thickness
7.2	Testing of current production
7.2.1	Sampling and testing
7.2.2	Length measurement
8	Report
8.1	Prototype rope
8.2	Current production
9	Certification
10	Marking, labelling and packaging
10.1	Marking

- 10.2 Labelling
- 10.3 Packaging

Annex A (normative) Fibre qualification and testing

- A.1 General
- A.2 Fibre specification
 - A.2.1 General information
 - A.2.2 Identification and general properties
 - A.2.3 Physical and mechanical properties
 - A.2.4 Yarn-on-yarn abrasion performance
- A.3 Fibre declaration
- A.4 Fibre testing
 - A.4.1 Fibre linear density and strength
 - A.4.2 Yarn-on-yarn abrasion performance
 - A.4.2.1 Qualification testing
 - A.4.2.1.1 Qualification testing (efficiency)
 - A.4.2.1.2 Qualification testing (persistence)
 - A.4.2.2 Testing of current production

Annex B (normative) Rope testing

- B.1 General
- B.2 Testing conditions
 - B.2.1 Rope samples
 - B.2.2 Ambient conditions
 - B.2.3 Testing machine
 - B.2.4 Load and elongation measurements
- B.3 Strength and stiffness test
 - B.3.1 Test procedure
 - B.3.2 Breaking strength
 - B.3.3 Load-elongation measurements
 - B.3.4 Dynamic stiffness at end of bedding-in
 - B.3.5 Quasi-static stiffness and dynamic stiffness
 - B.3.6 Calculation of mechanical properties
 - B.3.6.1 Core tenacity
 - B.3.6.2 Dynamic stiffness at the end of bedding-in
 - B.3.6.3 Dynamic stiffness
 - B.3.6.4 Quasi-static stiffness
- B.4 Linear density
 - B.4.1 Test procedure
 - B.4.2 Calculation of linear densities
- B.5 Cyclic loading endurance test
 - B.5.1 Planning
 - B.5.2 Test procedure
- B.6 Torque measurement
 - B.6.1 Torque factor
 - B.6.2 Torsional compatibility
- B.7 Particle ingress resistance

Annex C (informative) Guidance for rope handling care

- C.1 General considerations
- C.2 Presentation of rope on reels
- C.3 Reel lifting and handling
- C.4 Reel storage and maintenance
- C.5 Installation
 - C.5.1 Deployment overboard
 - C.5.2 Line tensions and re-reeling
 - C.5.3 Equipment condition
 - C.5.4 Rollers and rope bending
 - C.5.5 Pre-tensioning and hook-up
- C.6 Identifying damage
 - C.6.1 Damage to the rope cover
 - C.6.2 Damage to the rope core

Annex D (informative) Manufacturer declaration — Fibre ropes for offshore stationkeeping

Annex E (informative) Additional information and guidance

- E.1 Scope (Clause 1)**
- E.2 Type of construction (6.2)**
- E.3 Protective cover (6.4)**
- E.4 Length of rope (6.6)**
- E.5 Breaking strength (B.3.2)**
- E.6 Dynamic stiffness at end of bedding-in, dynamic and quasi-static stiffness (B.3)**
- E.7 Cyclic loading endurance test (B.5)**
- E.8 Length measurement and calculation of linear densities (B.4.2)**
- E.9 Quasi-static stiffness and dynamic stiffness (B.3.5)**
- E.10 Particle ingress protection (B.7)**
- E.11 Testing sequences (B.3 to B.5)**

Page count: 47