

ISO 19636:2019 (E)

Ships and marine technology — General requirements for inclinometers used for the determination of trim and list of LNG carriers

Contents

	Foreword	
	Introduction	
1	Scope	
2	Normative references	
3	Terms and definitions	
4	Safety precautions	
4.1	Existing safety regulations, standards and classification societies rules	
4.2	Equipment precautions	
5	Design requirements	
5.1	General	
5.2	A Trim and list inclinometer's axes and range	
5.3	Communication methods	
5.3.1	Analogue current interface type	
5.3.2	Digital interface type	
5.4	Levelling of a trim and list inclinometer	
5.5	A trim and list inclinometer's protection box	
5.6	Sealing, security and unsealing	
5.7	Marking serial number	
6	Installation	
6.1	General	
6.2	Installation of a trim and list inclinometer	
6.3	Alignment of a trim and list inclinometer	
6.4	Alignment of a trim and list inclinometer — Ship at dry dock	
6.5	Installation of a trim and list inclinometer — Ship at floating dock	
6.6	Installation of a trim and list inclinometer — Ship anchored or moored	
7	Accuracy	
7.1	General	
7.2	Uncertainty of a Trim and List inclinometer's inherent error - Factory acceptance test (FAT)	
7.3	Uncertainty of reference standard -Site acceptance test (SAT)	
7.4	Integrated overall accuracy	
8	Verification test and certification	
8.1	General	
8.2	Visual examination	
8.3	Verification test	
8.4	Sealing	
8.5	Certificate	
Annex A	(informative) Verification of alignment for trim and list inclinometers	
A.1	Alignment measurement for a trim and list inclinometer	
A.2	Error due to incorrect alignment	