ISO 19636:2019 (E)

Ships and marine technology — General requirements for inclinometers used for the determination of trim and list of LNG carriers

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Safety precautions

4.1 Existing safety regulations, standards and classification societies rules
4.2 Equipment precautions

5 Design requirements

5.1 General
5.2 A Trim and list inclinometer’s axes and range
5.3 Communication methods
5.3.1 Analogue current interface type
5.3.2 Digital interface type
5.4 Levelling of a trim and list inclinometer
5.5 A trim and list inclinometer’s protection box
5.6 Sealing, security and unsealing
5.7 Marking serial number

6 Installation

6.1 General
6.2 Installation of a trim and list inclinometer
6.3 Alignment of a trim and list inclinometer
6.4 Alignment of a trim and list inclinometer — Ship at dry dock
6.5 Installation of a trim and list inclinometer — Ship at floating dock
6.6 Installation of a trim and list inclinometer — Ship anchored or moored

7 Accuracy

7.1 General
7.2 Uncertainty of a Trim and List inclinometer's inherent error - Factory acceptance test (FAT)
7.3 Uncertainty of reference standard -Site acceptance test (SAT)
7.4 Integrated overall accuracy

8 Verification test and certification

8.1 General
8.2 Visual examination
8.3 Verification test
8.4 Sealing
8.5 Certificate

Annex A (informative) Verification of alignment for trim and list inclinometers

A.1 Alignment measurement for a trim and list inclinometer
A.2 Error due to incorrect alignment

Page count: 13