

# ISO 12215-5:2019 (E)

## Small craft — Hull construction and scantlings — Part 5: Design pressures for monohulls, design stresses, scantlings determination

---

### Contents

|       |   |
|-------|---|
|       | Foreword  |
|       | Introduction  |
| 1     | Scope   |
| 2     | Normative references  |
| 3     | Terms and definitions   |
| 4     | Symbols   |
| 5     | General   |
| 5.1   | Materials   |
| 5.2   | Overall procedure for scantlings determination                                      |
| 6     | Main dimensions, data and areas   |
| 6.1   | Dimensions and data   |
| 6.2   | Areas   |
| 6.2.1 | General   |
| 7     | Dimensions of panels and stiffeners   |
| 7.1   | General   |
| 7.2   | Rectangular grid of panels and stiffeners   |
| 7.3   | Non-rectangular panels  |
| 7.3.1 | Trapezoidal or triangular panels  |
| 7.3.2 | Other shapes  |
| 7.4   | Pressure on a panel or a stiffener  |
| 8     | Pressure adjusting factors  |
| 8.1   | General   |
| 8.2   | Design category factor $k_{DC}$   |
| 8.3   | Dynamic load factor $k_{DYN}$   |
| 8.4   | Longitudinal pressure distribution factor $k_L$                                     |
| 8.5   | Area pressure reduction factor $k_{AR}$   |
| 8.6   | Superstructures and deckhouse pressure reduction factor $k_{SUP}$                   |
| 8.7   | Pressure correcting factor $k_{SLS}$ for slamming of light and stable sailing craft |
| 9     | Design pressures  |
| 9.1   | Design pressure for motor craft   |
| 9.2   | Design pressure for sailing craft   |
| 9.3   | Watertight bulkheads and integral tank boundaries design pressure                   |
| 9.3.1 | General   |
| 9.3.2 | Integral tanks wash plates  |
| 9.3.3 | Collision bulkheads   |
| 9.3.4 | Non-watertight or partial bulkheads   |
| 9.3.5 | Centreboards of lifting keel wells  |
| 9.3.6 | Transmission of pillar loads  |
| 9.3.7 | Loads from outboard engines   |
| 10    | Mechanical properties and design stresses   |
| 10.1  | Boat building quality factor $k_{BB}$   |
| 10.2  | Assessment method factor $k_{AM}$   |

- 10.3 Design stresses according to material and calculation method
- 11 Methods for structural analysis and scantlings determination
  - 11.1 The six available methods
  - 11.2 Method 1: "Simplified" method
  - 11.3 Method 2: "Enhanced" method (ply by ply analysis)
  - 11.4 Method 3: "Developed" method for any laminate, including non-balanced laminates
  - 11.5 Method 4: "Direct test method"
  - 11.6 Method 5: "FEM" Finite Element Method
    - 11.6.1 General considerations
    - 11.6.2 General guidance for assessment by 3-D numerical procedures
    - 11.6.3 Boundary assumptions and load application
    - 11.6.4 Model idealisation
  - 11.7 Method 6: Alternative test: Drop test
  - 11.8 "Good practice" minimal thickness
- 12 Craft for professional use: Commercial craft and workboats
- 13 Owner's manual
  - 13.1 General
  - 13.2 Normal mode of operation
  - 13.3 Information to take care of sandwich plating
  - 13.4 Information required by Annex J for commercial craft and workboats
- 14 Application form

**Annex A (normative) Application of methods of analysis 1 to 3 of Table 18**

- A.1 Purpose of this Annex
- A.2 Panel assessment
  - A.2.1 General case: Dedicated and regularly spaced secondary stiffeners
  - A.2.2 Panel assessment in other cases
- A.3 Determination of the short dimension and curvature of a panel
- A.4 Very large panels
- A.5 Case where round bilged and hard chined panels act as "natural" stiffeners
  - A.5.1 General
  - A.5.2 Case a: For curved or U-shaped panels:
  - A.5.3 Case b: Where a centred circle can be inscribed in the bottom panel
  - A.5.4 Hard chined sections
- A.6 Examples of stiffener dimension assessment
  - A.6.1 General
  - A.6.2 Explanation of Figures A.4 a) to A.4 f)
- A.7 Calculation of the scantlings of a panel or stiffener across several areas
  - A.7.1 General
  - A.7.2 Examples of determination of panels or stiffeners with constant thickness or section modulus
  - A.7.3 Same example but with variable thickness or section modulus
  - A.7.4 Non-structural or redundant stiffeners
- A.8 Plating and stiffeners — Scantlings formulas for methods 1 to 3 of Table 2
  - A.8.1 Preliminary
  - A.8.2 Thickness adjustment factors for plating
    - A.8.2.1 Aspect ratio factors  $k_2$  for bending moment and shear force  $k_{SH}$
    - A.8.2.2 Curvature correction factor for plating
    - A.8.2.3  $k_C$
- A.9 Design shear force and bending moment on a rectangular panel
- A.10 Requirement for thickness or bending moment due to pressure
  - A.10.1 General
  - A.10.2 Use of bulking material and of "effective" core in bending
    - A.10.2.1 General
    - A.10.2.2 Resin-saturated foam/felt and syntactic foam
    - A.10.2.3 Plywood "cores" and other "effective" cores
  - A.10.3 Detail for assessment of metal plating
  - A.10.4 Detail for assessment of wood or plywood plating
- A.11 FRP sandwich plating
  - A.11.1 General

- A.11.2 Requirements for sandwich: Design stress in skins, core shear stress, and stability
- A.11.3 Local reinforcement of the inner skin to improve wrinkling resistance
- A.12 Requirements for stiffeners
  - A.12.1 General
  - A.12.2 Shear force and bending moment due to pressure loads
  - A.12.3 Stresses in stiffeners
  - A.12.4 Curvature factor for stiffeners  $kCS$
  - A.12.5 Attached plating effective breadth  $b_e$
  - A.12.6 Overall dimensions of stiffeners
    - A.12.6.1 Geometry
    - A.12.6.2 Maximum proportions between dimensions within a stiffener
    - A.12.6.3 Connection between the stiffener and the plating
- A.13 Structural bulkheads
  - A.13.1 General
- A.14 Structural support for sailing craft ballast keel
  - A.14.1 General
  - A.14.2 Reminder of requirements of ISO 12215-9

**Annex B (normative) Mechanical properties and design stress of metals**

**Annex C (normative) FRP laminates properties and calculations**

- C.1 Status of this Annex
- C.2 Determination of the mechanical properties
  - C.2.1 Tests and test standards
  - C.2.2 Topics on tests and calculation
  - C.2.3 Use of flexural strain and strength
  - C.2.4 Mechanical properties for the simplified method
  - C.2.5 Elastic constants using 'CLT' method (classical laminate theory)
  - C.2.6 Elastic constants using 'SRM' method (simplified regression method)
  - C.2.7 Final mechanical properties
  - C.2.8 Breaking strains — Both methods CLT or SRM
  - C.2.9 Practical use of CLT & SRM methods
    - C.2.9.1 Preliminary
    - C.2.9.2 Use of CLT and SRM methods
  - C.2.10 Ply thickness
- C.3 Final calculation of E, G and ultimate stress
  - C.3.1 General calculation
  - C.3.2 Builder's responsibility
- C.4 Determination of mechanical properties of materials not quoted in Tables C.5 to C.10
  - C.4.1 General
  - C.4.2 Example

**Annex D (normative) Drop test for craft <6 m**

- D.1 Theoretical background
  - D.1.1 Theory of drop test
  - D.1.2 Wave conditions
  - D.1.3 Relative impact speed
  - D.1.4 Verification of "drop height"
  - D.1.5 Safety margin
  - D.1.6 Fatigue
- D.2 Test and compliance
  - D.2.1 General
  - D.2.2 Test procedure
  - D.2.3 Inspection and pass/fail requirements

**Annex E (normative) Sandwich calculations**

- E.1 Sandwich formulas
  - E.1.1 General
- E.2 Sandwich pre-calculated tables and figures

**Annex F (normative) Wood/plywood laminate properties and calculations**

- F.1 Wood laminates
  - F.1.1 General
  - F.1.2 Plywood

- F.1.3 Moulded in-situ veneers
- F.1.4 Strip planking
- F.2 Wood laminate mechanical properties
- F.2.1 Tested properties
- F.2.2 Non-tested properties
- F.3 Laminated wood calculation examples

**Annex G (normative) Geometric properties of stiffeners**

- G.1 General
- G.2 Glass-reinforced plastic
- G.2.1 General
- G.2.2 "Squat" former top hats
- G.2.3 "Square" former top hats
- G.2.4 "Tall" former top hats
- G.3 Metal hull stiffeners
- G.4 Wood stiffeners
- G.4.1 General
- G.4.2 Wood stiffeners pre-calculated tables
- G.4.3 Method to assess wood stiffeners

**Annex H (normative) Laminate stack analysis for plating and stiffeners**

- H.1 General
- H.1.1 Presentation
- H.2 Calculation of the parameters for a panel
- H.2.1 Geometric aspect ratio, ARG, and effective aspect ratio, ARE
- H.2.2 Presentation of Table H.2
- H.2.3 Cells/columns (1) to (24) in Table H.2: Preliminary calculation: Shear force and bending moment
- H.2.4 Cells (25) to (60) in Table H.2 Panel laminate analysis
- H.2.5 Bending stiffness EI
- H.2.6 Bending stress analysis
- H.2.7 Shear stress analysis
- H.2.8 Example shown in Table H.2
- H.2.9 General topics
- H.3 Sandwich plating
- H.3.1 Core only taking shear load
- H.3.2 Core effective in bending
- H.3.3 Presentation of Tables H.3 and H.4
- H.4 Stiffener analysis — Tables H.5 to H.8
- H.4.1 General
- H.4.2 Tables H.6 to H.8 Worked example for a top hat stiffener

**Annex I (informative) "Good practice " values for minimum thickness or dry fibre mass**

- I.1 Background
- I.2 " Good practice" values for minimum thickness or fibre dry mass

**Annex J (normative) Commercial craft and workboats — Additional requirements**

- J.1 Types of commercial craft and workboats
- J.2 Additional requirements for commercial craft and workboats
- J.2.1 General
- J.2.2 Requirements for heavy duty workboats
- J.3 Owner's manual
- J.3.1 General
- J.3.2 Speed reduction table for heavy duty workboats

**Annex K (informative) Loads induced by outboard engines**

- K.1 Loads induced by outboard engines supports

**Annex L (informative) Application form of ISO 12215-5**