

ISO 20233-2:2019 (E)

Ships and marine technology — Model test method for propeller cavitation noise evaluation in ship design — Part 2: Noise source localization

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Model test setup and conditions |
| 5 | Noise measurement instrumentation |
| 5.1 | Hydrophone array |
| 5.1.1 | General |
| 5.1.2 | Hydrophone |
| 5.1.3 | Array types |
| 5.1.4 | Array setup |
| 5.1.5 | Array calibration |
| 5.2 | Data acquisition |
| 5.2.1 | General |
| 5.2.2 | Sampling frequency |
| 5.2.3 | Resolution |
| 5.2.4 | Synchronization for multiple channel sampling |
| 5.2.5 | Filtering |
| 5.2.6 | Acquisition time |
| 6 | Noise measurement procedure |
| 6.1 | Propeller cavitation noise measurement |
| 6.2 | Background noise measurement |
| 6.3 | Reference field measurement |
| 7 | Post processing |
| 7.1 | Array signal processing |
| 7.1.1 | Bartlett processor |
| 7.1.2 | MV processor |
| 7.1.3 | Other option for the processors |
| 7.2 | Graphical display of the output |
| 7.3 | Spatial resolution |
| Annex A | (informative) Hydrophone array design method |
| Annex B | (informative) Signal model for array signal processing |