

ISO 6218:2019 (E)

Inland navigation vessels — Manually- and power-operated coupling devices for rope connections of pushing units and coupled vessels — Safety requirements and main dimensions

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Safety requirements
4.1	General
4.1.1	Components
4.1.2	General requirements
4.2	Limitation of the actuating power for power-operated coupling devices
4.3	Strength requirements
5	Models
5.1	Operation
5.2	Position of handwheel/motor
5.3	With or without tensioning device
6	Design
6.1	Rope drum
6.1.1	Drum capacity
6.1.2	Drum diameter
6.1.3	Rope fastening
6.2	Handwheel
6.2.1	Clearances
6.2.2	Construction
6.2.3	Handhold
6.3	Power-operated equipment
6.4	Combined operating modes
6.5	Arresting device
6.5.1	General
6.5.2	Arresting devices for manually operated coupling devices
6.5.3	Arresting devices for power-operated coupling devices
6.6	Protective device
6.7	Footbrakes for manually operated coupling devices
6.8	Brakes for power-operated coupling devices
6.9	Gears
6.10	Tensioning device for manually operated coupling systems
6.11	Change gear for manually operated coupling devices
6.12	Foundation
6.13	Guide track
7	Dimensions and characteristic values
7.1	General
7.2	Characteristic values
7.3	Main dimensions of the coupling device
7.3.1	Manually operated coupling device
7.3.2	Power-operated coupling devices
7.4	Foundation

- 8** **Material**

- 9** **Operating instructions and assembly instructions**
 - 9.1** **General**
 - 9.2** **Assembly instructions**
 - 9.3** **Operating instructions**

- 10** **Designation — Examples**

- 11** **Marking**

- Annex A** **(normative) Individual and type testing**
 - A.1** **Selection of samples for type testing**
 - A.2** **Visual examination**
 - A.3** **Loading test**
 - A.3.1** **General**
 - A.3.2** **Test for manually operated coupling devices**
 - A.3.3** **Test for power-operated coupling devices**

Page count: 15