

DIN EN ISO 12215-10:2021-05 (E)

Small craft - Hull construction and scantlings - Part 10: Rig loads and rig attachment in sailing craft (ISO 12215-10:2020)

Contents		Page
European foreword		4
Foreword		5
Introduction		6
1	Scope	7
2	Normative references	7
3	Terms and definitions	7
4	Symbols	9
5	Application of the document	10
5.1	General	10
5.2	The simplified method	10
5.3	The developed method	10
5.4	Steps of the methods and corresponding clauses of this document	11
6	Simplified and developed methods -- Design stresses	12
6.1	General	12
6.2	Design load vs safety factor	13
7	Developed method -- General assessments, design moment	14
7.1	General	14
7.1.1	General topics on rigging design	14
7.1.2	Sail configurations:	15
7.1.3	Rigging loads and adjustment information to be provided	15
7.2	Design moment MD: righting or heeling moment	16
7.2.1	General	16
7.2.2	Principle of design	16
7.2.3	Topics on multihulls/form stable sailing craft corresponding to case b) i.e. with $MH1 < MR UP1$	19
7.2.4	Downwind longitudinal force FADOWN and nose trimming moment MHDOWN, running under spinnaker alone -- "Normal" (Sc6) or "exceptional" (Sc8)	20
7.2.5	Maximum righting moment MRMAX, exceptional case, reaching under spinnaker	20
7.2.6	Heeling force FABROACH and heeling moment MHBROACH while broaching under spinnaker, exceptional case	20
7.2.7	Minimum sail configuration and righting/heeling moment to be analyzed	20
7.3	Rig dimensions, and default values for areas, forces and points of application	21
7.4	Wing masts	27
7.5	Resultant forces in sails	28
8	Loads in rigging elements -- Developed method	29
8.1	General	29
8.2	Force in forestay, inner forestay, mainsail leech and on halyards	29
8.2.1	General	29
8.2.2	Force in forestay, inner forestay, mainsail leech and on halyards connected with sag	30
8.2.3	Force in forestay to balance the longitudinal component of forces from aft set shrouds, fixed/running backstays, mainsail leech	30

8.3	Force in backstay, running backstays, or equivalent	30
8.3.1	General	30
8.3.2	Fractional rig with fixed backstay, no running backstay and aft angled spreaders	31
8.3.3	Case of rigs without fixed nor running backstay	31
8.4	Compression in the mast step/pillar	33
8.4.1	General	33
8.4.2	Initial mast compression due to pre-stressing	33
8.4.3	Mast compression due to heeling or broaching	34
8.4.4	Design compression in the mast step/pillar	34
8.4.5	Detail topics on mast step/pillar	34
8.5	Final design load on rig elements	34
9	Structural components to be assessed--Simplified or developed method	35
9.1	General	35
9.2	Mast steps and mast pillars and their connection to the craft's structure	35
9.3	Chainplates and their connections to the craft's structure	35
9.4	Design details of chainplates and their connection to the structure	36
9.4.1	General	36
9.4.2	Strapped FRP chainplates	36
10	Application of the simplified method	37
11	Application of the developed method	37
11.1	General	37
11.2	General guidance for assessment by 3-D numerical procedures	37
11.2.1	General	37
11.2.2	Material properties	38
11.2.3	Boundary assumptions	38
11.2.4	Load application	38
11.2.5	Model idealization	38
11.3	Assessment by 'strength of materials' based methods	38
12	Application of this document	38
13	Information in the owner's manual	38
14	Information to the boat builder	39
	Annex A (informative) Application sheet of ISO 12215-10	40
	Annex B (informative) Information on metals and bolts	42
	Annex C (normative) Simplified "established practice" for mast step/pillar assessment	46
	Annex D (normative) Simplified "established practice" for the assessment of chainplates and their connection	53
	Annex E (informative) Simplified "established practice" calculation of transverserig elements -- Examples	75
	Bibliography	83