

# ISO 16273:2020 (E)

## Ships and marine technology — Night vision equipment for high-speed craft — Operational and performance requirements, methods of testing and required test results

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Performance requirements
4.1	Functions and their availability
4.2	Continuous operation
4.3	Standard test target
4.4	Detection range
4.5	Field of view
4.6	Pan and tilt ranges of the field of view
4.7	Speeds of panning of the field of view
4.8	Stabilisation of the field of view against the motions of the vessel
4.9	Heading marker indication
4.10	Clear view
4.11	Roll and pitch
4.12	Optical interference
4.13	Line of sight
4.14	Controls and ergonomics
4.15	Presentation of information
4.16	Software
4.17	Durability and resistance to environmental conditions
4.18	Electrical and electromagnetic interference
4.19	Power supply
4.20	Back up and fall back arrangements
4.21	Malfunctions, alerts and indications
4.22	Interfacing
4.23	Safety precautions
4.24	Acoustic noise and signals
4.25	Compass safe distance
4.26	Active illumination for active image intensifier system
5	Methods of testing and required test results
5.1	General test conditions
5.1.1	General
5.1.2	Performance test
5.1.3	Performance check
5.1.4	Performance check (EMC)
5.2	Environmental tests
5.2.1	General
5.2.2	Sensor shock test
5.2.2.1	General
5.2.2.2	Procedure
5.2.2.3	Methods of testing and required results
5.2.3	Roll and pitch test
5.2.4	Optical interference test

5.2.5	Line of sight test
5.3	Interface test
5.4	Further laboratory tests
5.4.1	General
5.4.2	Test for all types of night vision equipment
5.4.2.1	General
5.4.2.2	Presentation of information
5.4.2.3	Back up and fall back arrangements
5.4.2.4	Continuous operation test
5.4.2.5	Field of view test
5.4.2.6	Pan and tilt ranges as well as speeds of panning of the field of view test, and heading marker indication test
5.4.2.7	Clear view test
5.4.2.8	Wind endurance test
5.4.3	Test of thermal imaging systems
5.4.3.1	Thermal imaging system
5.4.3.2	Range prediction test
5.4.4	Test of active image-intensifier systems
5.4.4.1	General
5.4.4.2	Illuminator spectrum
5.4.4.3	Image-intensifier sensor
5.4.4.4	Infrared illuminators
5.4.4.5	Range prediction
5.5	Sea trials
5.5.1	Introduction
5.5.2	Standard test target
5.5.3	Test conditions
5.5.4	Test procedures
5.5.4.1	General
5.5.4.2	Detection-range evaluation test
5.5.4.3	Optical interference test
6	Marking and identification
7	Installation
8	Maintenance
9	Documentation
Annex A	(informative) Range prediction calculation
Annex B	(informative) Infrared illuminator, typical plots
Annex C	(informative) Sea trial record
C.1	General data
C.2	Equipment identity
C.3	Trial installation details
Annex D	(normative) Measurement of MTDP (minimum temperature difference perceived) of thermal imagers
D.1	Validity
D.2	Definition of MTDP
D.3	Measurement conditions
D.4	Measurement process
D.5	Exploitation of results
Annex E	(normative) Stabilisation test for thermal imaging systems
Annex F	(normative) Stabilisation test active image-intensifier systems