

ISO 12215-7:2020 (E)

Small craft — Hull construction and scantlings — Part 7: Determination of loads for multihulls and of their local scantlings using ISO 12215-5

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	Application of this document
5.1	Materials
5.2	Limitations
5.3	Overall procedure for the application of this document
6	Main dimensions, data and areas
6.1	Dimensions and data
6.1.1	General
6.1.2	Bottom deadrise of the hulls β_x and chine beam BC_x of planing multihulls
6.1.3	Wet deck bottom
6.1.4	Crossbeams
6.2	Areas
7	Dimensions and pressure for panels and stiffeners under local loads
7.1	General
7.2	Example of application on multihulls
7.2.1	Sections
7.2.2	Details on panel assessment and dimensions
7.2.3	The constant averaged pressure method
7.2.4	Other assessment and dimensioning methods
7.2.5	Panels acting as "natural" stiffeners
7.3	Other topics on panel or stiffener dimensions
8	Local pressure-adjusting factors
9	Local design pressures
9.1	General
9.2	Limits of areas
9.3	Tables defining the local design pressures for multihulls
9.4	Design pressure for trimaran floats $PTRF_x$
9.4.1	Pressure reduction factors
9.4.2	Pressure
9.5	Design pressure on watertight bulkheads and integral tanks
10	Further treatment of structural elements subject to local loads
11	Assessment of multihulls rudders, appendages and their wells
12	Multihull global loads
12.1	General
12.2	Typical structural arrangements

- 12.3 Global load assessment
 - 12.3.1 General
 - 12.3.2 The simplified method
 - 12.3.2.1 Global loads for the simplified method
 - 12.3.3 The enhanced method
 - 12.4 Design stresses under global loads
 - 12.5 Global load case GLC1: Diagonal load in quartering sea
 - 12.6 Global load case GLC 2: Rig loads
 - 12.7 Combination of diagonal load GLC 1 and rig load GLC 2 for sailing multihulls
 - 12.8 Global load case GLC 3: Asymmetric broaching loads in sailing multihulls
 - 12.9 Global load case GLC 4: Longitudinal broaching/pitchpoling
 - 12.9.1 General
 - 12.9.2 Full method of analysis of the buoyancy load when the craft pitchpoles
 - 12.10 Global load case GLC 5: Longitudinal force on one hull
 - 12.10.1 General
 - 12.10.2 Longitudinal force
 - 12.11 Global load case GLC 6: Bending of crossbeams connecting hulls for motor catamarans.
- 13 Structural arrangement for supporting global loads
 - 14 Multihulls used as commercial craft and workboats
 - 15 Information to be included in the owner's manual
 - 15.1 General
 - 15.2 Respect of maximum loaded displacement
 - 15.3 Operational guidance
 - 15.4 Information to take care of sandwich plating
 - 15.5 Information required by Annex J of ISO 12215-5:2019 - for commercial craft and workboat
- Annex A (informative) Application sheet of ISO 12215-7**
- Annex B (informative) "Established practice" recommendations for global loads assessment using FEM methods and reporting**
- B.1 Examples of "Established practices"
 - B.2 Guidelines for reporting the structural analysis with FEM method
- Annex C (informative) "Established practice" details**
- C.1 Details for the connection of crossbeams with the hulls
 - C.2 Design stresses
 - C.3 Analysis of beams
 - C.3.1 General
 - C.3.2 Method of analysis
 - C.3.3 Dimensions, sections, neutral axis
 - C.3.4 Shear buckling analysis
 - C.3.4.1 Single skin shear buckling
 - C.3.4.2 Sandwich shear buckling
 - C.3.5 Compression buckling and skins stability
 - C.3.6 Eventual cut-out in the web
 - C.3.6.1 Shear stress
 - C.3.6.2 Secondary bending moment
- Annex D (informative) Technical background and example of torsional moment analysis with differential deflection of crossbeams**
- D.1 General
 - D.2 Theory
 - D.3 Worked example
 - D.3.1 General
 - D.3.2 Full method
 - D.3.3 Special case of two cross-beams only (suitable for small sports sailing catamarans)
 - D.3.4 General case of more than 2 cross-beams
 - D.3.5 Special case of a continuous cross-structure as found in some motor catamarans
 - D.3.6 Recommended application of this annex