ISO 12215-7:2020 (E)

Small craft — Hull construction and scantlings — Part 7: Determination of loads for multihulls and of their local scantlings using ISO 12215-5

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols

5 Application of this document

5.1 Materials
5.2 Limitations
5.3 Overall procedure for the application of this document

6 Main dimensions, data and areas

6.1 Dimensions and data
6.1.1 General
6.1.2 Bottom deadrise of the hulls βx and chine beam BCx of planing multihulls
6.1.3 Wet deck bottom
6.1.4 Crossbeams
6.2 Areas

7 Dimensions and pressure for panels and stiffeners under local loads

7.1 General
7.2 Example of application on multihulls
7.2.1 Sections
7.2.2 Details on panel assessment and dimensions
7.2.3 The constant averaged pressure method
7.2.4 Other assessment and dimensioning methods
7.2.5 Panels acting as "natural" stiffeners
7.3 Other topics on panel or stiffener dimensions

8 Local pressure-adjusting factors

9 Local design pressures

9.1 General
9.2 Limits of areas
9.3 Tables defining the local design pressures for multihulls
9.4 Design pressure for trimaran floats PTRFx
9.4.1 Pressure reduction factors
9.4.2 Pressure
9.5 Design pressure on watertight bulkheads and integral tanks

10 Further treatment of structural elements subject to local loads

11 Assessment of multihulls rudders, appendages and their wells

12 Multihull global loads

12.1 General
12.2 Typical structural arrangements

12.3 Global load assessment
12.3.1 General
12.3.2 The simplified method
12.3.2.1 Global loads for the simplified method
12.3.3 The enhanced method
12.4 Design stresses under global loads
12.5 Global load case GLC1: Diagonal load in quartering sea
12.6 Global load case GLC 2: Rig loads
12.7 Combination of diagonal load GLC 1 and rig load GLC 2 for sailing multihulls
12.8 Global load case GLC 3: Asymmetric broaching loads in sailing multihulls
12.9 Global load case GLC 4: Longitudinal broaching/pitchpoling
12.9.1 General
12.9.2 Full method of analysis of the buoyancy load when the craft pitchpoles
12.10 Global load case GLC 5: Longitudinal force on one hull
12.10.1 General
12.10.2 Longitudinal force
12.11 Global load case GLC 6: Bending of crossbeams connecting hulls for motor catamarans.

13 Structural arrangement for supporting global loads

14 Multihulls used as commercial craft and workboats

15 Information to be included in the owner's manual

15.1 General
15.2 Respect of maximum loaded displacement
15.3 Operational guidance
15.4 Information to take care of sandwich plating
15.5 Information required by Annex J of ISO 12215-5:2019 - for commercial craft and workboat

Annex A (informative) Application sheet of ISO 12215-7

Annex B (informative) "Established practice" recommendations for global loads assessment using FEM methods and reporting

B.1 Examples of "Established practices"
B.2 Guidelines for reporting the structural analysis with FEM method

Annex C (informative) "Established practice" details

C.1 Details for the connection of crossbeams with the hulls
C.2 Design stresses
C.3 Analysis of beams
C.3.1 General
C.3.2 Method of analysis
C.3.3 Dimensions, sections, neutral axis
C.3.4 Shear buckling analysis
C.3.4.1 Single skin shear buckling
C.3.4.2 Sandwich shear buckling
C.3.5 Compression buckling and skins stability
C.3.6 Eventual cut-out in the web
C.3.6.1 Shear stress
C.3.6.2 Secondary bending moment

Annex D (informative) Technical background and example of torsional moment analysis with differential deflection of crossbeams

D.1 General
D.2 Theory
D.3 Worked example
D.3.1 General
D.3.2 Full method
D.3.3 Special case of two cross-beams only (suitable for small sports sailing catamarans)
D.3.4 General case of more than 2 cross-beams
D.3.5 Special case of a continuous cross-structure as found in some motor catamarans
D.3.6 Recommended application of this annex