

ISO 12217-2:2022-12 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 2: Sailing boats of hull length greater than or equal to 6 m

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 3.1 | Primary | 2 |
| 3.2 | Hazards | 4 |
| 3.3 | Downflooding | 4 |
| 3.4 | Dimensions, areas and angles | 5 |
| 3.5 | Condition, mass and volume | 6 |
| 3.6 | Other terms and definitions | 9 |
| 4 | Symbols | 12 |
| 5 | Procedure | 13 |
| 5.1 | Maximum load | 13 |
| 5.2 | Sailing or non-sailing | 13 |
| 5.3 | Tests, calculations and requirements to be applied | 13 |
| 5.4 | Variation in input parameters | 14 |
| 6 | Requirements for monohull boats | 14 |
| 6.1 | Requirements to be applied | 14 |
| 6.2 | Downflooding | 15 |
| 6.2.1 | Downflooding openings | 15 |
| 6.2.2 | Downflooding height | 18 |
| 6.2.3 | Downflooding angle | 19 |
| 6.3 | Recess size | 19 |
| 6.3.1 | Application | 19 |
| 6.3.2 | Simplified methods | 20 |
| 6.3.3 | Direct calculation method | 22 |
| 6.4 | Minimum righting energy | 22 |
| 6.5 | Angle of vanishing stability | 23 |
| 6.5.1 | General | 23 |
| 6.5.2 | Normal requirement | 23 |
| 6.5.3 | Alternative requirement for design category B | 23 |
| 6.6 | Stability index (STIX) | 24 |
| 6.6.1 | Method | 24 |
| 6.6.2 | Dynamic stability factor (FDS) | 25 |
| 6.6.3 | Inversion recovery factor (FIR) | 25 |
| 6.6.4 | Knockdown recovery factor (FKR) | 25 |
| 6.6.5 | Displacement-length factor (FDL) | 26 |
| 6.6.6 | Beam-displacement factor (FBD) | 26 |
| 6.6.7 | Wind moment factor (FWM) | 26 |
| 6.6.8 | Downflooding factor (FDF) | 27 |
| 6.6.9 | Calculation of the stability index (STIX) | 27 |
| 6.7 | Knockdown-recovery test | 27 |
| 6.8 | Wind stiffness test | 28 |

| | | |
|--|--|----|
| 6.8.1 | General | 28 |
| 6.8.2 | Practical test | 28 |
| 6.8.3 | Compliance by calculation | 30 |
| 6.8.4 | Requirements | 31 |
| 6.9 | Flotation requirements | 32 |
| 6.10 | Capsize-recovery test | 32 |
| 6.11 | Detection and removal of water | 34 |
| 7 | Requirements for catamarans, trimarans and form-stable monohulls | 35 |
| 7.1 | Requirements to be applied | 35 |
| 7.2 | Downflooding openings | 35 |
| 7.3 | Downflooding height | 35 |
| 7.4 | Recess size | 35 |
| 7.5 | Stability information | 35 |
| 7.6 | Safety signs | 36 |
| 7.7 | Bare poles factor | 37 |
| 7.8 | Rolling in breaking waves | 37 |
| 7.9 | Pitchpoling | 38 |
| 7.10 | Diagonal stability | 38 |
| 7.11 | Habitable multihull boats | 38 |
| 7.12 | Buoyancy when inverted | 40 |
| 7.13 | Escape after inversion | 41 |
| 8 | Safety signs | 42 |
| 9 | Application | 42 |
| 9.1 | Deciding the design category | 42 |
| 9.2 | Meaning of the design categories | 42 |
| Annex A (normative) Full method for required downflooding height | | 44 |
| Annex B (normative) Methods for calculating downflooding angle | | 46 |
| Annex C (normative) Determining the curve of righting moments | | 48 |
| Annex D (normative) Method for calculating reserve of buoyancy after inversion or swamping | | 51 |
| Annex E (normative) Flotation material and elements | | 53 |
| Annex F (normative) Information for the craft's owner's manual | | 55 |
| Annex G (normative) Determination of safe wind speed information | | 59 |
| Annex H (normative) Determination of longitudinal righting characteristics | | 62 |
| Annex I (informative) Summary of requirements | | 65 |
| Annex J (informative) Worksheets | | 68 |
| Annex K (informative) Illustration of recess retention level | | 87 |
| Bibliography | | 88 |