ISO 12217-2:2022-12 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 2: Sailing boats of hull length greater than or equal to 6 m

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 2
3.1 Primary 2
3.2 Hazards 4
3.3 Downflooding 4
3.4 Dimensions, areas and angles 5
3.5 Condition, mass and volume 6
3.6 Other terms and definitions 9

4 Symbols 12

5 Procedure 13
5.1 Maximum load 13
5.2 Sailing or non-sailing 13
5.3 Tests, calculations and requirements to be applied 13
5.4 Variation in input parameters 14

6 Requirements for monohull boats 14
6.1 Requirements to be applied 14
6.2 Downflooding 15
6.2.1 Downflooding openings 15
6.2.2 Downflooding height 18
6.2.3 Downflooding angle 19
6.3 Recess size 19
6.3.1 Application 19
6.3.2 Simplified methods 20
6.3.3 Direct calculation method 22
6.4 Minimum righting energy 22
6.5 Angle of vanishing stability 23
6.5.1 General 23
6.5.2 Normal requirement 23
6.5.3 Alternative requirement for design category B 23
6.6 Stability index (STIX) 24
6.6.1 Method 24
6.6.2 Dynamic stability factor (FDS) 25
6.6.3 Inversion recovery factor (FIR) 25
6.6.4 Knockdown recovery factor (FKR) 25
6.6.5 Displacement-length factor (FDL) 26
6.6.6 Beam-displacement factor (FBD) 26
6.6.7 Wind moment factor (FWM) 26
6.6.8 Downflooding factor (FDF) 27
6.6.9 Calculation of the stability index (STIX) 27
6.7 Knockdown-recovery test 27
6.8 Wind stiffness test 28

6.8.1 General 28
6.8.2 Practical test 28
6.8.3 Compliance by calculation 30
6.8.4 Requirements 31
6.9 Flotation requirements 32
6.10 Capsize-recovery test 32
6.11 Detection and removal of water 34

7 Requirements for catamarans, trimarans and form-stable monohulls 35
7.1 Requirements to be applied 35
7.2 Downflooding openings 35
7.3 Downflooding height 35
7.4 Recess size 35
7.5 Stability information 35
7.6 Safety signs 36
7.7 Bare poles factor 37
7.8 Rolling in breaking waves 37
7.9 Pitchpoling 38
7.10 Diagonal stability 38
7.11 Habitable multihull boats 38
7.12 Buoyancy when inverted 40
7.13 Escape after inversion 41

8 Safety signs 42

9 Application 42
9.1 Deciding the design category 42
9.2 Meaning of the design categories 42

Annex A (normative)Fullmethodforrequireddownfloodingheight 44

Annex B (normative)Methodsforcalculatingdownfloodingangle 46

Annex C (normative) Determining the curve of righting moments 48

Annex D (normative) Method for calculating reserve of buoyancy after inversion or swamping 51

Annex E (normative) Flotation material and elements 53

Annex F (normative) Information for the craft's owner's manual 55

Annex G (normative) Determination of safe wind speed information 59

Annex H (normative) Determination of longitudinal righting characteristics 62

Annex I (informative) Summary of requirements 65

Annex J (informative) Worksheets 68

Annex K (informative) Illustration of recess retention level 87

Bibliography 88