

DIN EN ISO 12217-2:2026-04 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 2: Sailing boats of hull length greater than or equal to 6 m (ISO 12217-2:2022)

Contents		Page
Foreword		v
Introduction		vi
1 Scope		1
2 Normative references		1
3 Terms and definitions		2
3.1 Primary.....		2
3.2 Hazards.....		4
3.3 Downflooding.....		4
3.4 Dimensions, areas and angles.....		5
3.5 Condition, mass and volume.....		6
3.6 Other terms and definitions.....		9
4 Symbols		12
5 Procedure		13
5.1 Maximum load.....		13
5.2 Sailing or non-sailing.....		13
5.3 Tests, calculations and requirements to be applied.....		13
5.4 Variation in input parameters.....		14
6 Requirements for monohull boats		14
6.1 Requirements to be applied.....		14
6.2 Downflooding.....		15
6.2.1 Downflooding openings.....		15
6.2.2 Downflooding height.....		18
6.2.3 Downflooding angle.....		19
6.3 Recess size.....		19
6.3.1 Application.....		19
6.3.2 Simplified methods.....		20
6.3.3 Direct calculation method.....		22
6.4 Minimum righting energy.....		22
6.5 Angle of vanishing stability.....		23
6.5.1 General.....		23
6.5.2 Normal requirement.....		23
6.5.3 Alternative requirement for design category B.....		23
6.6 Stability index (STIX).....		24
6.6.1 Method.....		24
6.6.2 Dynamic stability factor (FDS).....		25
6.6.3 Inversion recovery factor (FIR).....		25
6.6.4 Knockdown recovery factor (FKR).....		25
6.6.5 Displacement-length factor (FDL).....		26
6.6.6 Beam-displacement factor (FBD).....		26
6.6.7 Wind moment factor (FWM).....		26
6.6.8 Downflooding factor (FDF).....		27
6.6.9 Calculation of the stability index (STIX).....		27
6.7 Knockdown-recovery test.....		27
6.8 Wind stiffness test.....		28
6.8.1 General.....		28

6.8.2	Practical test.....	28
6.8.3	Compliance by calculation.....	30
6.8.4	Requirements.....	31
6.9	Flotation requirements.....	32
6.10	Capsize-recovery test.....	32
6.11	Detection and removal of water.....	34
7	Requirements for catamarans, trimarans and form-stable monohulls	35
7.1	Requirements to be applied.....	35
7.2	Downflooding openings.....	35
7.3	Downflooding height.....	35
7.4	Recess size.....	35
7.5	Stability information.....	35
7.6	Safety signs.....	36
7.7	Bare poles factor.....	37
7.8	Rolling in breaking waves.....	37
7.9	Pitchpoling.....	38
7.10	Diagonal stability.....	38
7.11	Habitable multihull boats.....	38
7.12	Buoyancy when inverted.....	40
7.13	Escape after inversion.....	41
8	Safety signs	42
9	Application	42
9.1	Deciding the design category.....	42
9.2	Meaning of the design categories.....	42
Annex A	(normative) Full method for required downflooding height	44
Annex B	(normative) Methods for calculating downflooding angle	46
Annex C	(normative) Determining the curve of righting moments	48
Annex D	(normative) Method for calculating reserve of buoyancy after inversion or swamping	51
Annex E	(normative) Flotation material and elements	53
Annex F	(normative) Information for the craft's owner's manual	55
Annex G	(normative) Determination of safe wind speed information	59
Annex H	(normative) Determination of longitudinal righting characteristics	62
Annex I	(informative) Summary of requirements	65
Annex J	(informative) Worksheets	68
Annex K	(informative) Illustration of recess retention level	87
Bibliography	88