ISO 12217-3:2002-05 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 3: Boats of hull length less than 6 m

Contents

Page

1 Scope 1

2 Normative references 1

3 Terms and definitions 2
3.1 Primary 2
3.2 Downflooding 3
3.3 Condition and mass 3
3.4 Other definitions 4

4 Symbols 6

5 Procedure 6
5.1 Maximum total load 6
5.2 Sailing or non-sailing 6
5.3 Tests to be applied 7
5.4 Alternatives 7

6 Tests to be applied to non-sailing boats 7
6.1 General 7
6.2 Downflooding-height tests 8
6.3 Offset-load test 12
6.4 Level flotation test 13
6.5 Basic flotation test 14
6.6 Capsize-recovery test 14

7 Tests to be applied to sailing boats 15
7.1 General 15
7.2 Downflooding-height tests 16
7.3 Flotation tests 16
7.4 Capsize-recovery test 16
7.5 Knockdown-recovery test 17
7.6 Wind stiffness test 18

8 Application 19
8.1 Deciding the design category 19
8.2 Meaning of the design categories 19

Annex A (normative) Full method for required downflooding height 20

Annex B (normative) Method for flotation tests 22

Annex C (normative) Flotation material and elements 27

Annex D (normative) Calculation method for basic flotation requirement 29

Annex E (normative) Information for owner's manual 31

Annex F (informative) Summary of requirements 32

Annex G (informative) Worksheets 34

Bibliography 47