

ISO 12217-3:2002-05 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 3: Boats of hull length less than 6 m

Contents		Page
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
3.1	Primary	2
3.2	Downflooding	3
3.3	Condition and mass	3
3.4	Other definitions	4
4	Symbols	6
5	Procedure	6
5.1	Maximum total load	6
5.2	Sailing or non-sailing	6
5.3	Tests to be applied	7
5.4	Alternatives	7
6	Tests to be applied to non-sailing boats	7
6.1	General	7
6.2	Downflooding-height tests	8
6.3	Offset-load test	12
6.4	Level flotation test	13
6.5	Basic flotation test	14
6.6	Capsize-recovery test	14
7	Tests to be applied to sailing boats	15
7.1	General	15
7.2	Downflooding-height tests	16
7.3	Flotation tests	16
7.4	Capsize-recovery test	16
7.5	Knockdown-recovery test	17
7.6	Wind stiffness test	18
8	Application	19
8.1	Deciding the design category	19
8.2	Meaning of the design categories	19
Annex A (normative) Full method for required downflooding height		20
Annex B (normative) Method for flotation tests		22
Annex C (normative) Flotation material and elements		27
Annex D (normative) Calculation method for basic flotation requirement		29
Annex E (normative) Information for owner's manual		31
Annex F (informative) Summary of requirements		32
Annex G (informative) Worksheets		34
Bibliography		47