

ISO/TS 17321-4:2016-06 (E)

Graphic technology and photography - Colour characterization of digital still cameras (DSCs) - Part 4: Programmable light emission system

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Requirements	2
4.1	General	2
4.2	Hardware requirements	3
4.2.1	General	3
4.2.2	Operating condition	4
4.2.3	Specifications of the system	4
4.2.4	Time stability and long-term stability of light intensity	7
4.3	Figure of merit for a colour target using a programmable light emission system	9
4.3.1	General	9
4.3.2	Terms and notations of SR2	9
4.3.3	Method for the calculation of SR2	10
4.3.4	Figure of merit	11
4.4	Report	11
Annex A (informative) Integrating sphere method and LED-driving method		13
Annex B (informative) Spectral power distribution optimization procedure for multiple LEDs		15
Annex C (informative) The need for constraints on the average values and maximum values of SR2 and CIEDE2000		19
Annex D (informative) Evaluation method for light source generated by a programmable light emission system		21
Annex E (informative) SR2 and CIEDE2000 recommendations for colorimetric image capture		24
Annex F (normative) SR2L and SR2 calculation methods for a light emission system in which spectral distribution is only obtained by measurements		26
Bibliography		28